Rittal – The System.

Faster – better – everywhere.

Digital enclosure internal temperature display and thermostat – SK 3114.200

Date : May 27, 2017

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Digital enclosure internal temperature display and thermostat – SK 3114.200

created: 27.05.2017 build on www.rittal.com/us-en



Product description

Description:	For installation in the enclosure door or wall.
Technical specifications:	Three-digit, 7-segment display Option of switching between °C/°F. With 1800 mm long NTC sensor Two relay outputs as change-over contact and normally open contact (max. contact load 230 V, 6 A). Freely selectable switching difference.
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 54

Product features

Rated operating voltage:	100 V - 230 V, 1~, 50 Hz/60 Hz 24 V - 60 V (DC)
Installation depth:	100 mm
Temperature range:	Operation (environment): +0°C...+50°C Setting range: +5°C...+55°C
Packaging unit:	1 pc(s).
Weight/packaging unit:	0.26 kg (0.6 lb.)

© Rittal 2017

EAN:	4028177631434
Customs tariff number:	90321020
ETIM 6.0:	EC002014
ETIM 5.0:	EC002014
eCl@ss 8.0/8.1:	27210707
eCl@ss 7.0/7.1:	27210707
eCl@ss 6.0/6.1:	27210707
eCl@ss 5.1/5.1.4:	27180792
Product description (long):	SK Digital temperature display and thermostat, 100-230 V, 1~, 50/60 Hz, 24-60 V (DC), Installation depth: 100 mm

Approvals

Approvals:	UR
Certificates:	EAC
Declarations:	Declaration of conformity

2017 © Rittal Corporation