Date: 11/04/2023

F73.100/4, -20...+80°C, L1=250 mmx10mm,

Gas actuated thermometer, stainless steel series

Item number: 48786979

Quantity: 1 pcs.

Order code: F73.100-CBC-4ND-E0250-N10-1-Z-H1Z-ZZZZZZ G7 FZZZEVZDIWS-AZ1ZZZZZ2ZZZZ

Overview:
F73.100/4, -20...+80°C, L1=250 mmx10mm,
1/2 NPT radial bottom
Surface mounting flange, stainless steel
standard capillary stainless steel 1.4571
Capillary length: 10 m
laminated safety glass
class 1 per EN 13190
liquid damping
Silicon oil M50
WIKA
with Serial number

Details:
Gas actuated thermometer, stainless steel series
Specifications according to data sheet: TM 73.01
Case: stainless steel
Stem material: stainless steel
Model: F73.100, nominal size 100, with capillary
Unit: °C
Scale range: -20 °C ... +80 °C
Damping: liquid damping
Connection design: 4, compression fitting, sliding on stem
Process connection: 1/2 NPT
Stem diameter: 10 mm
Insertion length L1: 250 mm
Capillary: standard capillary stainless steel 1.4571
Capillary length: 10 m
Design of case mounting: Surface mounting flange, stainless steel
Ignition protection type: without
Zone: without
Accuracy class: class 1 per EN 13190
Case filling fluid: Silicon oil M50
Ingress protection: IP 65
Window: laminated safety glass
Case: Stainless steel
Connector location: radial bottom
Manufacturer logo: *WIKA*
Permissible ambient temperature: -40 … +60 °C
with Serial number

© 2023 - WIKA Instruments s.a.r.l.