Specifications

Eaton CH222DU



Catalog Number: CH222DU

Fuse accessory, Fuse-holder, low voltage, 125 A, AC 690 V, 22 x 58 mm, 2P, IEC, UL, C22M and C22G fuses, IEC 60269-1, IEC 60269-2, IP20

General specifications

Product Name
Eaton Bussmann series low voltage cylindrical fuse holder

Catalog Number
CH222DU

EAN
5027590497060

UPC
051712685399

Product Length/Depth
77 mm

Product Height
123 mm

Product Width
71 mm

Product Weight
275 g

Compliances
CE Marked
RoHS Compliant

Certifications
IEC 60269-2
EAC
IEC 60269-1
UL Listed File E14853

Powering Business Worldwide

Product specifications

Used with

C22G, C22M, FWP-(amps)A22F fuses

Type

fuse accessory

Application

Industrial and Commercial applications

Amperage Rating

125 A

Number of Poles

Two-pole

Width in number of modular spacings

3

Built-in depth

51.5 mm

Fuse size

22 x 58 mm

Operating temperature details

-20ºC to +70ºC

Voltage rating at AC

690 V a.c. (IEC) and 700 V a.c. (UL)

Voltage rating at DC

1000 V d.c. (IEC)

Fuse type

C22G

C22M

Lockable

Yes

Accessories

JV-L Multipole connector kit, CH22-CTP IP20 Protection accessory

Torque rating

Min 4 Nm/ Max 5 Nm

Concurrently switching N-neutral

No

Material

Polyester

Resources

Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

CA134002EN

Declarations of conformity

UKCA Modular fuse-holders

CE Modular fuse-holders

Multimedia

Eaton Bussmann – Modular fuse holders

Technical data sheets

10115 22 x 58 mm Modular fuse holder

10080 14 x 51 mm Modular fuse holder

720147 10 x 38 mm Modular fuse holder

Optical defect indication

No

Mounting method

DIN rail

2 x M4 Panel mounting screws

Degree of protection

IP20

Voltage rating

690 V

Model

CH22

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia