LV Ventilation Fans



Description

A range of slim and stylish ventilation fans suitable for bathrooms, toilets and kitchens.

Features

- Fan is suitable for installation in Zone 1 of Bathrooms
- Transformer needs 240V supply and should be installed outside Zone 2
- Low energy fans – meet Building Regulation L1A specific fan power of less than 0.5W/l/s
- Low noise fans – meet Building Regulation F1 by being under 35dB for less noise sensitive rooms
- Over run timers factory set at 15 minutes
- Humidistat factory set at 75% RH
- Ideal for through wall applications or with ducting lengths under 2m
- Fans have a one shot thermal fuse
- 3-year guarantee

Range

4” (100mm) Timer	4616
4” (100mm) Timer & Humidistat	4617

Technical Specification

	4”
Extraction rate	24 l/s (85m³/hr)
Specific Fan Power	0.34W (l/s)
Noise level	28dB @ 3m
Voltage	12Vac
Motor Rating	8W
IP Rating	IP 24
Ambient Temp	40°C Max.
Insulation Class	Double Insulated
Over Run Timer	2-30mins.
Humidistat	60-90% RH
Dimensions	150 x 150 x 19

No user serviceable parts

Standards

- BS EN 60335-2-80

Deta Electrical Company Ltd.
UK: Panattoni Park Luton Road Chalton Bedfordshire LU4 9TT UK
EU: Unit 16 Ashbourne Industrial Estate Ashbourne Co. Meath A84 W972 Ireland
Tel. +44 1582 544 548 technical@deta.co.uk