

ADV-031-14-16-E-C2

THERMOELECTRIC MODULE





MID LEVEL PERFORMANCE - VALUE ORIENTED

31 couple, 20x20x3.8mm, 6Amp

Features

- ROHS & REACH Compliant
- Precise temperature control
- Solid-state reliability

Applications

Automotive, Industrial,
Telecommunications, Medical, Aerospace


CHARACTERISTICS		
DeltaT at 300K	[°C]	70
Vmax	[V]	4.0
Imax	[A]	6.2
Qmax	[W]	13.7
A	[mm]	20
A1	[mm]	20
B	[mm]	20
Flatness/Parellelism	[mm]	0.05 / 0.05


- (At hot side temperature Th = 25°C / 298K, under dry N_2)
- Pc max = Cooling power at ΔT = 0 and I = Imax
- ΔTmax = Temperature difference at I = Imax and Pc = 0
- Max hot side temperature Th = 90°C for best long term performance
- Max mounting pressure: 1.5MPa
- Wires: UL rated wire to 105°C


Adaptive is a registered trademark of European Thermodynamics Limited.
Web: www.etdyn.com | Tel: +44(0)116 279 6899
E-mail: info@etdyn.com


ADV-031-14-16-E-C2

Hot side temperature 25 degrees C













Hot side temperature 50 degrees C












Adaptive is a registered trademark of European Thermodynamics Limited.
Web: www.etdyn.com | Tel: +44(0)116 279 6899
E-mail: info@etdyn.com


ADV-031-14-16-E-C2

Hot side temperature 75 degrees C









Adaptive is a registered trademark of European Thermodynamics Limited.
Web: www.etdyn.com | Tel: +44(0)116 279 6899
E-mail: info@etdyn.com