DATASHEET - CSAU-01/01-16IE

Switching Actuator 16A with input, energy measurement

Part no.	**CSAU-01/01-16IE**
	172942
EL Number (Norway)	**4560733**

General specifications	
Product name	Eaton Moeller series xComfort switching actuator
Part no.	CSAU-01/01-16IE
EAN	4015081695300
Product Length/Depth	65 millimetre
Product height	18 millimetre
Product width	65 millimetre
Product weight	0.044 kilogram
Compliances	RoHS conform
Product Tradename	xComfort
Product Type	Switching actuator
Product Sub Type	None
Delivery program	
Actuation function	Switching
Amperage rating	16 A
Bus system operating type	Radio frequent xComfort
Bus system product type	Actuator
Technical Data - Electrical	
Rated operating voltage (Ue) - min	230 V
Rated operating voltage (Ue) - max	230 V
Switching current - max	16 A
Power supply	Mains
Output power	3680 W
Switching power - max	3680 W
Power consumption	0.25 W
Technical Data - Mechanical	
Width in number of modular spacings	3
Mounting method	Flush mounted (plaster) Flush mounting
Number of inputs (binary)	1
Degree of protection	IP20
Additional information	
Features	Radio frequent bidirectional Local operation/hand operation
Fitted with:	Bus connection LED indication
Functions	Bus module detachable
Suitable for	C-load

Technical data ETIM 9.0

Installation bus systems (EG000032) / Switch actuator for bus system (EC001097)

Electric engineering, automation, process control engineering / Electrical installation, device / Bus system / Switch actuator for bus system (ecl@ss13-27-14-31-25 [AKE293019])

Bus system KNX	No
Bus system KNX-RF (Radio Frequent)	No
Bus system radio frequent	Yes
Bus system LON	No
Bus system Powernet	No
Other bus systems	xComfort

Radio frequent bidirectional		Yes
Mounting method		Flush-mounted
Width in number of modular spacings		3
Local operation/hand operation		Yes
With LED indication		Yes
Number of digital inputs		1
Max. switching power	W	3680
Max. switching power LED	W	0
Output power	W	3680
Suitable for C-load		Yes
Max. number of switching contacts		1
Max. switching current	A	16
Rated current	A	16
Rated operating voltage	V	230 - 230
Different phases connectable		No
Power consumption	W	0.25
With bus connection		Yes
Bus module detachable		Yes
Min. depth of built-in installation box	mm	18
Modular expandability		No
Degree of protection (IP)		IP20

© 04/2023 by Eaton Industries GmbH