PRODUCT-DETAILS

OS1250B03N3P

OS1250B03N3P SWITCH FUSE



General Information

Extended Product Type	OS1250B03N3P
Product ID	1SCA107936R1001
EAN	6417019413945
Catalog Description	OS1250B03N3P SWITCH FUSE
Long Description	Switch Fuses,Front Operated,4-pole,03 (Left Side),British Standard,D1,Handle and shaft included,Detachable Neutral Link Integrated Into the Mechanism

ABB EcoSolutions

Environmental Product Declaration - EPD	1SCC311203D0201
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available

Material Compliance

Conflict Minerals Reporting Template	9AKK108467A5658

© 2024 ABB. All rights reserved.

(CMRT)	
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	1SCC011025D0201

Popular Downloads

Data Sheet, Technical Information	1SCC311013C0201
Instructions and Manuals	1SCC311022M0207
Environmental Product Declaration - EPD	1SCC311203D0201

Environmental

Pollution Degree	3

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Dimensions

Product Net Width	429 mm
Product Net Height	356 mm
Product Net Depth / Length	366 mm
Product Net Weight	30.21 kg 66.6 lb

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	394 mm 15.51 in
Package Level 1 Depth / Length	534 mm 21.02 in
Package Level 1 Height	368 mm 14.49 in
Package Level 1 Gross Weight	32.46 kg 71.56 lb
Package Level 1 EAN	6417019413945

Technical

Conventional Free-air Thermal Current (I_{th})	Θ = 40 °C 1250 A
Conventional Thermal Current (I_{the})	Fully Enclosed 1000 A

© 2024 ABB. All rights reserved.

Fourth Pole Type	Detachable Neutral Link Integrated Into the Mechanism
Fuse Size	D1
Fuse System	British Standard
Handle Type	Pistol handle and shaft included
Mounting Type	Base mounting
Number of Poles	3P
Operating Mode	Front Operated
Pollution Degree	3
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Power Loss	at Rated Operating Conditions per Pole 75 W
Rated Conditional Short-Circuit Current (I_{nc})	(690 V) 80 kA
Rated Current (I_n)	Main Circuit 1250 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 1250 A (500 V) 1250 A (690 V) 1250 A
Rated Operational Current AC-21B (I_e)	(500 V) 1250 A (690 V) 1250 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 1250 A
Rated Operational Current AC-22B (I_e)	(500 V) 1250 A (690 V) 1250 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 1000 A
Rated Operational Current AC-23B (I_e)	(500 V) 1000 A (690 V) 1000 A
Rated Operational Power AC-23A (P_e)	(220 ... 240 V) 315 kW (400 V) 560 kW (415 V) 560 kW (500 V) 710 kW (690 V) 1000 kW
Rated Operational Voltage	Main Circuit 690 V AC
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 40 kiloampere rms
Special Functions	Detachable Neutral
Standards	IEC 60947-3
Switches Operating Mechanism	03 (Left Side)
Terminal Type	Lug terminals
Terminal Width	50 mm
Tightening Torque	50 ... 75 N·m

Technical UL/CSA

Tightening Torque	50 ... 75 N·m

Certificates and Declarations

A2L Certificate – IEC	1SCC311210D0201

© 2024 ABB. All rights reserved.

ATEX Certificate	No certification needed
CCC Certificate	CCC OS1200-1250 2015.pdf
Declaration of Conformity - CE	1SCC311127D2703
DNV GL Certificate	1SCC311131D0203
UL Certificate	No certification needed

Classifications

Object Classification Code	Q
ETIM 8	EC001040 - Fuse switch disconnector
ETIM 9	EC001040 - Fuse switch disconnector
UNSPSC	39122233
IDEA Granular Category Code (IGCC)	5291 >> Fuse switch disconnector
eClass	V11.1 : 27371401
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3661014

Categories

Low Voltage Products and Systems → Switches → Switch Fuses



© 2024 ABB. All rights reserved.