Date: 24/04/2023

232.30.100 40 barg 1/2 NPT lower mount

Bourdon Tube Pressure Gauges, Safety Pattern

Item number: 48803238

Quantity: 1 pcs.

Order code: 232.30-E-8G440Z-ND-UZHZCZH-ZZZ1ZZZ 213D31ZI3W0 12Z-IZZZZZZ12ZZZ
CERT22-EF2D-AA-FA-GA- - - - - - - - -
CERT31-EF2D-AB-BB- - - - - - - - -
LABEL-PG1DE-ZZZZZ

Overview: 232.30.100 40 barg 1/2 NPT lower mount
Measuring System 316L
Ingress protection: IP 65
for oxygen, oil and grease free
class 1.0
Window: laminated safety glass
Permissible medium temperature: + 200 °C
Permissible ambient temperature: -40 … +60 °C
with thread protection
Pressure Gauge Standard: International (standard Europe)
WIKA
with Serial number
Test report 2.2 per EN 10204
Certificate Language: English and French
Certificate for: pressure gauge
Formal certificate: Manufactured according to state-of-the-art
Ingress protection: Ingress protection IP65
Technical specification: Oxygen service
Inspection certificate 3.1 per EN 10204
Certificate type: Inspection certificate acc. to DIN EN 10204 3.1
Certificate Language: English and French
Certificate for: pressure gauge
Accuracy: Calibration values listed
Material certificate: Wetted parts material (metal contents) with mill certificate incl. chemical analysis
Label: WIKA standard without / with Tag-number

Details: Bourdon Tube Pressure Gauges, Safety Pattern
Series EN 837-1
Model: 232.30
Specifications according to data sheet: PM 02.04
Measuring system: stainless steel
Case filling: without
Nominal size: 100 mm
Measuring range: gauge pressure range

© 2023 - WIKA Instruments s.a.r.l.

Scale range: 0...40 barg
Process connection: 1/2 NPT
Connector location: lower mount
Window: laminated safety glass
Pointer: standard pointer
Special design features: for oxygen, oil and grease free
Accuracy class: class 1.0
Overpressure safe: standard
Case material: Stainless steel 1.4301
Case surface: bare
Material pressure element: Measuring System 316L
Case filling fluid: prepared for filling
Ingress protection: IP 65
Permissible medium temperature: + 200 °C
Permissible ambient temperature: -40 … +60 °C
Movement: stainless steel
Thread protection: with thread protection
Packaging: single packing
Pressure Gauge Standard: International (standard Europe)
Manufacturer logo: *WIKA*
with Serial number
Permissible ambient temperature: -40 … +60 °C
Test report 2.2 per EN 10204
Certificate Language: English and French
Certificate for: pressure gauge
Formal certificate: Manufactured according to state-of-the-art
Ingress protection: Ingress protection IP65
Technical specification: Oxygen service
Inspection certificate 3.1 per EN 10204
Certificate type: Inspection certificate acc. to DIN EN 10204 3.1
Certificate Language: English and French
Certificate for: pressure gauge
Accuracy: Calibration values listed
Material certificate: Wetted parts material (metal contents) with mill certificate incl. chemical analysis

© 2023 - WIKA Instruments s.a.r.l.