Date: 12/04/2023

MWBXXUR - 0...60 mbar - Adaptor 1/2 NPT-M - 1/2 -14 NPT-F

Diaphragm pressure switch, Stainless steel case

Item number: 48763969

Quantity: 1 pcs.

Order code: MWBXXUR-MAISB-2AMZZZZZZZZZZZZZZZZZZZZZZ ZCK1BW

Overview:
MWBXXUR - 0...60 mbar - Adaptor 1/2 NPT-M - 1/2 -14 NPT-F
Diaphragm pressure switch, Stainless steel case
measuring elements and wetted materials: Diaphragm AISI 316, 304, Inconel or Hastelloy (Piston AISI 316)/ Process Connection AISI 316L
Contact version: 1x SPDT silver contact, adjustable dead band
setting range: 0...60 mbar
Standard, working range = 0...60 mbar, proof pressure 300 mbar
Process connection: Adaptor 1/2 NPT-M
Electrical connection: 1/2 -14 NPT-F
Enclosure with plate for wall or direct mounting
Ingress Protection: IP66
Diaphragm: Stainless Steel AISI 316/O-Ring: PTFE/Connection: Stainless steel AISI 316L
Brand: WIKA Instruments Italia
Specifications according to data sheet: PV 31.10
Repeatability of set point: ≤ 1% of span

Set point definition: Set Point not defined

Details:
Diaphragm pressure switch, Stainless steel case
Model MW
Specifications according to data sheet: PV 31.10
Repeatability of set point: ≤ 1% of span
Contact version: 1x SPDT silver contact, adjustable dead band
setting range: 0...60 mbar
working range: Standard, working range = 0...60 mbar, proof pressure 300 mbar
Set Point not defined
Unit: mbar
Process connection: Adaptor 1/2 NPT-M
Electrical connection: 1/2 -14 NPT-F
Enclosure with plate for wall or direct mounting
Brand: WIKA Instruments Italia
Ingress Protection: IP66
MWBXXUR
Diaphragm: Stainless Steel AISI 316/O-Ring: PTFE/Connection: Stainless steel AISI 316L

© 2023 - WIKA Instruments s.a.r.l.