Date: 11/04/2023

TW20 P=26.7 mm G 1/2 female U=73 mm B=0.437 inch (11.1 mm) SS316/316L

Socket weld Thermowell TW20, solid machined

Item number:	48759797
Quantity:	1 pcs.
Order code:	TW20-B-M-2-TD-00073-00040-G3-T-3-0190-0190-ZZ-Z-Z00106 Z001061ZYQ3Z
Overview:	TW20 P=26.7 mm G 1/2 female U=73 mm B=0.437 inch (11.1 mm) SS316/316L Welding diameter: 26.7 mm Connection to thermometer [N]: G 1/2 female Thermowell style: Straight Head length [H]: 40 mm Insertion length [U]: 73 mm Root diameter [Q]: 19 mm Tip diameter [V or F3]: 19 mm Bore size [B or d1]: 0.437 inch (11.1 mm) Bore depth / stem length (US) [A]: 106 mm Plug option: SS plug & chain Specifications according to data sheet: TW 95.20
Details:	Socket weld Thermowell TW20, solid machined Specifications according to data sheet: TW 95.20 Thermowell style: Straight Unit of measure: Metric (mm) Welding diameter: 26.7 mm (for 3/4 inch pipe) Connection to thermometer [N]: G 1/2 female Insertion length [U]: 73 mm Head length [H]: 40 mm Material: Stainless steel 316/316L Bore size [B or d1]: 0.437 inch (11.1 mm) Pressure rating: Class 3000 Root diameter [Q]: 19 mm Tip diameter [V or F3]: 19 mm Bore depth / stem length (US) [A]: 106 mm Plug option: SS plug & chain Tip thickness [Tt]: 0.250 inch (6.4 mm)

© 2023 - WIKA Instruments s.a.r.l.