Date: 11/04/2023

TW20 P=26.7 mm 1/2 NPT female U=150 mm B=0.335 inch (8.5 mm) SS316/316L

Socket weld Thermowell TW20, solid machined

Item number:	48758486
Quantity:	1 pcs.
Order code:	TW20-A-M-2-UD-00150-00060-G3-M-3-0190-0171-ZZ-Z-Z00203 Z00203ZZYQ3Z
Overview:	TW20 P=26.7 mm 1/2 NPT female U=150 mm B=0.335 inch (8.5 mm) SS316/316L Welding diameter: 26.7 mm Connection to thermometer [N]: 1/2 NPT female Thermowell style: Tapered Head length [H]: 60 mm Insertion length [U]: 150 mm Root diameter [Q]: 19 mm Tip diameter [V or F3]: 17.1 mm Bore size [B or d1]: 0.335 inch (8.5 mm) Bore depth / stem length (US) [A]: 203 mm Specifications according to data sheet: TW 95.20
Details:	Socket weld Thermowell TW20, solid machined Specifications according to data sheet: TW 95.20 Thermowell style: Tapered Unit of measure: Metric (mm) Welding diameter: 26.7 mm (for 3/4 inch pipe) Connection to thermometer [N]: 1/2 NPT female Insertion length [U]: 150 mm Head length [H]: 60 mm Material: Stainless steel 316/316L Bore size [B or d1]: 0.335 inch (8.5 mm) Pressure rating: Class 3000 Root diameter [Q]: 19 mm Tip diameter [V or F3]: 17.1 mm Bore depth / stem length (US) [A]: 203 mm Tip thickness [Tt]: 0.250 inch (6.4 mm)

© 2023 - WIKA Instruments s.a.r.l.