Date: 11/04/2023

TR36, PT100-2w, cl.B, G1/2 fixed, 50 mm x 8 mm

TR36 resistance thermometer in compact version

Item number: 48807026

Quantity: 1 pcs.

Order code: TR36-ZZZZ-P2-ZLZZZZZZZZZZZZ-1380050-ZZZ-FAA-ZZ R36 0060ZPZZZZWIKA0Z

Overview: TR36, PT100-2w, cl.B, G1/2 fixed, 50 mm x 8 mm

Output signal: PT100-2w, cl.B
Electrical connection: Angled plug - DIN EN 175301- 803 Form A

Process connection: Fixed threaded hex bushing G1/2 B
Process temperature: -50 ... +150°C
Sensor diameter ød: 8 mm
Insertion length A: 50 mm
Permissible ambient temperature: -40 ... +85 °C (-40 ... +185 °F)
Accessories electr. connection: Mating plug with blue sealing - DIN EN 175301-803 Form A
Pin assignment: Standard pin connection Pt-Sensors (see datasheet)

Specifications according to data sheet: TE 60.36

Details: TR36 resistance thermometer in compact version
Specifications according to data sheet: TE 60.36
Electrical connection: Angled plug - DIN EN 175301- 803 Form A
Output signal: Pt100 Class B (IEC 60751), 2-wire
Process temperature: -50 ... +150°C
Process connection: Fixed threaded hex bushing G1/2 B
Sensor diameter ød: 8 mm
Insertion length A: 50 mm
Permissible ambient temperature: -40 ... +85 °C (-40 ... +185 °F)
Accessories electr. connection: Mating plug with blue sealing - DIN EN 175301-803 Form A
Pin assignment: Standard pin connection Pt-Sensors (see datasheet)

© 2023 - WIKA Instruments s.a.r.l.