Date: 11/04/2023

A5500/4, NS100, 0...160°C, L1=276x8mm

Bimetal thermometer, stainless steel version

Item number: 48780962

Quantity: 1 pcs.

Order code: A5500 -4-C1K-ND-C276GZZ-AHAZZZZ TB FZZZEPZSVID-AZ1ZZZZZ1ZZZZ

Overview:
A5500/4, NS100, 0...160°C, L1=276x8mm
Process connection: 1/2 NPT, axial
flat instrument glass,
class 1 per EN 13190
Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X)
WIKA Serial number *...*

Details:
Bimetal thermometer, stainless steel version
Specifications according to data sheet: TM 55.01
Case: stainless steel
Stem material: stainless steel
Model: A 5500, nominal size 100, location of stem centre back (axial)
Connection design: 4, compression fitting, sliding on stem
Unit: °C
Scale range: 0 °C ... 160 °C
Process connection: 1/2 NPT
Stem diameter: 8 mm
Insertion length L1: 276 mm
Window: flat instrument glass
Zone: Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X)
Case: Stainless steel
Connector location: axial
Version: standard
Stem material: stainless steel
Permissible ambient temperature: -40 ... +70 °C
Manufacturer logo: *WIKA*
Accuracy class: class 1 per EN 13190
Ingress protection: IP 65
serial number on dial: Serial number *...*
Explosion protection: ATEX
Ignition protection type: Ex h

© 2023 - WIKA Instruments s.a.r.l.