Date: 25/04/2023

DPGS43.100...LM-F51 2.5 bar 2 x G 1/2 B

switchGAUGE DPGS43.100/160

Item number: 48643892

Quantity: 1 pcs.

Order code: DPGS43.100.23ZZZPZ-BG325Z-IHAB-LM-F51-ZZZIZ-ZZZZ 5UZZZ 33DDHZZISGZZ-ZZZZZZ11Z

Overview:
DPGS43.100...LM-F51 2.5 bar 2 x G 1/2 B
magnetic snap action switch, model 821.3
plug sidewise
Case: with pressure blowout disk
Connection location: lower mount
class 1.6
Ingress protection: IP 65
Case filling fluid: Silicon oil M50
max. static pressure: 25 bar
Overpressure safety: 25 bar
laminated safety glass
Permissible medium temperature: -20 ... +100 °C (-4 ... +212 °F)
Permissible ambient temperature: -20 … +60 °C
Pressure Gauge Standard: International (standard Europe)
WIKA Serial number *...*

Details:
switchGAUGE DPGS43.100/160
differential pressure gauge with switches,
all welded construction
Specifications according to data sheet: PV 27.05 and AC 08.01
switch: magnetic snap action switch, model 821
first switch operation: change over (3)
Electrical connection: plug sidewise
Nominal size: 100
Scale range: 0...2.5 bar
max. static pressure: 25 bar
Overpressure safety: 25 bar
Process connection: 2 x G 1/2 B
Connection location: lower mount
Liquid Damping (case filling): with
Case: pressure blowout disk
Pressure Gauge Standard: International (standard Europe)
Accuracy class: class 1.6
Case material: Stainless steel 1.4301
Case surface: bare
Case filling fluid: Silicon oil M50
Window: laminated safety glass
Ingress protection: IP 65

© 2023 - WIKA Instruments s.a.r.l.

Permissible medium temperature: -20 ... +100 °C (-4 ... +212 °F)
Permissible ambient temperature: -20 … +60 °C
Manufacturer logo: *WIKA*
serial number on dial: Serial number *...*

© 2023 - WIKA Instruments s.a.r.l.