

Soft chemical protection glove, dual colour and material - natural rubber and neoprene.

TEGERA® 2301

Learn more

LIGHTLY FLOCKED FOR EXTRA COMFORT

A lightly flocked, soft, and comfortable 0,7 mm/27,5 mil chemical protection glove, dual colour and material - natural rubber and neoprene. The glove has a diamond pattern for good grip, is approved for handling food stuffs (not fatty food) and is oil and grease resistant. Choose this glove for high level of protection, durability, flexibility, and comfort.

CHARACTERISTICS

- High level of protection
- Durable
- Flexible
- Comfortable
- Good grip
- Good fit

FUNCTIONS

- Waterproof
- Approved for handling foodstuffs
- Oil and grease resistant

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Corrosive injuries, contact with chemicals, contact with moisture, contact with damp

PRIMARY ENVIRONMENTS OF USE

Chemical risk environments, microbiological risk environments, environments hazardous to health, corrosive environments, wet environments, moist environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Chemical work, chemical technology work, laboratory work

PRIMARY INDUSTRIES OF USE

Agriculture, chemical, rubber and plastic

TYPE OF WORK

Medium weight

CHEMICAL RESISTANCE

According to EN16523-1:2015. For details, please contact Ejendals.

SPECIFICATION

TYPE Chemical protection gloves
CATEGORY Cat. III
THICKNESS 0,7* mm (*chem-layer)
LENGTH 320 mm
DEXTERITY 5
INSIDE Flock-lined
GRIP DESIGN Diamond grip pattern
COLOUR Blue, Yellow
PAIRS PER: BUNDLE/CARTON 12/120
AQL 1.5
DISPLAY TYPE Bulk pack
DIPPING MATERIAL Latex, Neoprene

COMPLIANCE

CE 0598

UKCA Cat. III

EAC

TP TC 019:2011

Information/UIS

EN 16523:2015 + A1:2018

LATEX

NOT FOR FATTY FOOD

EN ISO 374-1:2016/A1:2018 Type A
AKLMNPST

EN ISO 374-5:2016
Virus

EN 388:2016+A1:2018
2110X

EN ISO 21420:2020

FEATURES

Waterproof

Chemical protection

TEST ACCORDING TO EN ISO 374-1:2016

Tested chemical	A	K	L	M	N	P	S	T
Permeation level	2	6	3	5	2	6	6	6
Degradation %	4,9	-13,3	26,4	21,9	22,7	6,5	X	-1,6

SIZE		ARTICLE NUMBER	EAN
6	XS	2301-6	7340118353555
7	S	2301-7	7340118353647
8	M	2301-8	7340118353739
9	L	2301-9	7340118353821
10	XL	2301-10	7340118353913

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.