41 - Metric offset combination wrenches




Standards:

NF ISO 7738, ISO 7738, DIN 3113

Description:

- Offset combination wrenches: ring offset to clear fingers or obstacles. Ideal for series of nuts.
- OGV® profile with 12-point ring for powerful tightening while protecting the nut.
- Open end head angled at 15°.
- Metric sizes: 6 to 32 mm.
- Presentation: satin chrome finish.



© FACOM 2020

	A [mm]	Length L [mm]	Thickness E [mm]	Thickness E1 [mm]	Head Width B [mm]	Height H [mm]	Weight [Kg]
41.10	10.0	142.0	5.0	8.0	23.5	16.5	0.05
41.11	11.0	160.0	5.5	8.6	27.5	18.5	0.075
41.12	12.0	160.0	5.5	8.6	27.5	18.5	0.075
41.13	13.0	180.0	5.5	9.0	31.5	18.5	0.1
41.14	14.0	180.0	5.5	9.0	31.5	18.5	0.1
41.15	15.0	200.0	6.6	10.3	36.5	20.5	0.13
41.16	16.0	200.0	6.6	10.3	36.5	20.5	0.13
41.17	17.0	224.0	7.3	11.2	40.5	22.0	0.195
41.18	18.0	224.0	7.3	11.2	40.0	22.0	0.195
41.19	19.0	248.0	7.8	12.6	43.0	24.0	0.25
41.21	21.0	275.0	8.2	13.0	48.0	33.0	0.32
41.22	22.0	275.0	8.2	13.0	48.0	26.5	0.32
41.23	23.0	302.0	9.0	14.0	53.0	28.5	0.415
41.24	24.0	302.0	9.0	14.0	53.0	28.5	0.415
41.26	26.0	332.0	9.5	15.0	59.0	31.5	0.605
41.27	27.0	332.0	9.5	15.0	59.0	31.5	0.605
41.28	28.0	364.0	10.0	15.6	63.0	33.5	0.7
41.29	29.0	364.0	10.0	15.6	63.0	33.5	0.7
41.30	30.0	398.0	10.5	16.5	68.0	35.5	0.85
41.32	32.0	398.0	10.5	16.5	68.0	35.5	0.85
41.6	6.0	113.0	4.0	6.0	14.5	12.5	0.03
41.7	7.0	127.0	4.5	7.0	18.5	15.0	0.035
41.8	8.0	127.0	4.5	7.0	18.5	15.0	0.035
41.9	9.0	142.0	5.0	8.0	23.5	16.5	0.05

© FACOM 2020