Date: 24/04/2023

232.50.100 16 bar Diaphragm Seal lower mount

Bourdon Tube Pressure Gauges, Stainless Steel

Item number: 48765539

Quantity: 1 pcs.

Order code: DSS1-MS990.53-123X50-MK1M2-C7S65ZJ2-ZZAZZZZZ WA1-Z
LABEL-PG1DE-ZZZZZ- ZZZZZ
232.50-E-BG416Z-CA-UCHZAZZ-ZZZZZZZ 213D311IXX0 Z2Z-IZZZZZZ12ZZZ
H990.53-II138C2C2AZ505ZZZ Z

Overview: 232.50.100 16 bar Diaphragm Seal lower mount
Measuring System 316L Version 1 small volume (for diaphragm seals)
Ingress protection: IP 65
class 1.0
surface mounting flange, stainless steel
Window: laminated safety glass
adjustable pointer
Pressure Gauge Standard: International (standard Europe)
WIKA
with Serial number

Diaphragm seal system with 1 diaphragm seal
Assembly specification High-Side: 1 meter capillary; stainless steel
System fill fluid: KN 92 Medicinal white mineral oil; for pharmaceutical and food applications; FDA, USP, EP
Process temperature min.: + 10°C
Process temperature max.: + 80°C; for sterilisation (SIP) max. + 130°C
Ambient temperature pressure meas. min: + 10°C
Ambient temperature pressure meas. max: + 40°C

Diaphragm seal for hygienic applications
Clamp following ISO 2852
Model 990.53 DN 38 (pipe dimensions 38.0 x 1.2)
pipe standard: Pipe dimensions per ISO 2037 or BS 4825 part 1
Upper body material / main body material: Stainless steel 1.4435 (316L); UNS S31603
Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603
Surface roughness wetted parts, welding seam excluded: Ra ≤ 0,76 µm (Ra 0.30 µin.) according to ASME BPE SF3
Clamp diameter: 50.5 mm

Label: WIKA standard without / with Tag-number

© 2023 - WIKA Instruments s.a.r.l.

Date: 24/04/2023

Details:

Bourdon Tube Pressure Gauges, Stainless Steel
Series
Model: 232.50
Specifications according to data sheet: PM 02.02
Measuring system: stainless steel
Case filling: without
Nominal size: 100 mm
Scale range: 0...16 bar
Process connection: Diaphragm Seal
Connector location: lower mount
Mounting flange/bracket: surface mounting flange, stainless steel
Window: laminated safety glass
Pointer: adjustable pointer
Accuracy class: class 1.0
Overpressure safe: standard
Case material: Stainless steel 1.4301
Case surface: bare
Material pressure element: Measuring System 316L
Case filling fluid: prepared for filling
Special measuring element: Version 1 small volume (for diaphragm seals)
Ingress protection: IP 65
Movement: stainless steel
Packaging: single packing
Pressure Gauge Standard: International (standard Europe)
Manufacturer logo: *WIKA*
with Serial number
Diaphragm seal system with 1 diaphragm seal
Assembly specification High-Side: 1 meter capillary; stainless steel
System fill fluid: KN 92 Medicinal white mineral oil; for pharmaceutical and food applications; FDA, USP, EP
Process temperature min.: + 10°C
Process temperature max.: + 80°C; for sterilisation (SIP) max. + 130°C
Ambient temperature pressure meas. min: + 10°C
Ambient temperature pressure meas. max: + 40°C
Capillary inner diameter: ID 2mm (3x0.5 mm)
Diaphragm seal for hygienic applications
Specifications according to data sheet: DS 99.41
Diaphragm seal: Model 990.53
Process connection type: Clamp following ISO 2852
Process connection: DN 38 (pipe dimensions 38.0 x 1.2)
pipe standard: Pipe dimensions per ISO 2037 or BS 4825 part 1
Upper body material / main body material: Stainless steel 1.4435 (316L); UNS S31603
Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603
Surface roughness wetted parts, welding seam excluded: Ra ≤ 0,76 µm (Ra 0.30 µin.) according to ASME BPE SF3

© 2023 - WIKA Instruments s.a.r.l.

Clamp diameter: 50.5 mm

Label: WIKA standard without / with Tag-number

© 2023 - WIKA Instruments s.a.r.l.