Specifications

Eaton 086723



Catalog Number: 086723

Eaton xEnergy Safety Ci LV systems LV switchgear. Busbar terminal, for CU 3x40x10

General specifications

Product Name
Eaton xEnergy Safety Ci busbar enclosure accessory

Catalog Number
086723

EAN
4015080867234

Product Length/Depth
70 mm

Product Height
50 mm

Product Width
90 mm

Product Weight
0.1 kg

Compliances
RoHS conform

Powering Business Worldwide

Product specifications

Used with

Cu 3 x (40 mm x 10 mm) busbars
Prepared enclosures
Ci insulated enclosure
Accessory for busbar enclosures

Special features

For main conductor L1, L2, L3

Type

Accessory for busbar enclosures
Ci insulated enclosure
Prepared enclosures

Accessory/spare part type

Busbar terminals

Width clamp

50 mm

Busbar thickness - max

10 mm

Busbar thickness - min

10 mm

Busbar width - max

40 mm

Busbar width - min

40 mm

Conductor cross section - max

1200 mm²

Rated operational current (Ie) - max

1600 A

Functions

Connection for flat cable and cu bar

Suitable for

Flat rail
Strip conductor connection

Rated operational current

1600 A

Terminal capacity (flat strip)

Resources

Brochures

eaton-xenergy-safety-ci-subway-line-success-story-en-us.pdf

eaton-xenergy-safety-ci-enclosure-brochure-br014001en-en-us.pdf

Catalogs

eaton-xenergy-ci-safety-catalog-ca015006en-en-us.pdf

Drawings

eaton-insulated-boards-busbar-xenergy-safety-ci-busbar-terminal-3d-drawing-004.eps

50 mm x 12 mm (2x)

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia