Date: 24/04/2023

233.30.100 10 bar Diaphragm Seal lower mount

Bourdon Tube Pressure Gauges, Safety Pattern

Item number: 48794706

Quantity: 1 pcs.

Order code: DSS1-MF990.27-123X30-DZZZD-C8K65ZA1-ZZAZZZZZ WAZ-Z
LABEL-PG1DE-ZZZZZ- ZZZZZ
233.30-E-BG410Z-CA-UZHZAZZ-ZZZZZZZ 213D3A1IXX0 Z2Z-IZZZZZZ12ZZZ
H990.27-ASM1521BC1-C1-C2ZZZZZ Z

Overview: 233.30.100 10 bar Diaphragm Seal lower mount
Measuring System 316L Version 1 small volume (for diaphragm seals)
Ingress protection: IP 65
class 1.0
Window: laminated safety glass
adjustable pointer
Case filling fluid: glycerine
Pressure Gauge Standard: International (standard Europe)
WIKA
with Serial number

Diaphragm seal system with 1 diaphragm seal
Assembly specification High-Side: Direct assembly
System fill fluid: KN 2 Silicone oil for general applications
Process temperature min.: 0°C
Process temperature max.: + 90°C
Ambient temperature pressure meas. min: + 10°C
Ambient temperature pressure meas. max: + 40°C

Diaphragm seal, flange type, flush diaphragm
Model 990.27 1 1/2" Class 300 following ASME B16.5
Upper body material / main body material: Stainless steel 1.4404 (316L); UNS S31603
Sealing face: RF 125...250 AA
Sealing face material: Stainless steel 1.4404 (316L); UNS S31603
Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603

Label: WIKA standard without / with Tag-number

Details: Bourdon Tube Pressure Gauges, Safety Pattern
Series EN 837-1
Model: 233.30
Specifications according to data sheet: PM 02.04

© 2023 - WIKA Instruments s.a.r.l.

Measuring system: stainless steel
Case filling: with
Nominal size: 100 mm
Measuring range: gauge pressure range
Scale range: 0...10 bar
Process connection: Diaphragm Seal
Connector location: lower mount
Window: laminated safety glass
Pointer: adjustable pointer
Accuracy class: class 1.0
Overpressure safe: standard
Case material: Stainless steel 1.4301
Case surface: bare
Material pressure element: Measuring System 316L
Case filling fluid: glycerine
Special measuring element: Version 1 small volume (for diaphragm seals)
Ingress protection: IP 65
Movement: stainless steel
Packaging: single packing
Pressure Gauge Standard: International (standard Europe)
Manufacturer logo: *WIKA*
with Serial number
Diaphragm seal system with 1 diaphragm seal
Assembly specification High-Side: Direct assembly
System fill fluid: KN 2 Silicone oil for general applications
Process temperature min.: 0°C
Process temperature max.: + 90°C
Ambient temperature pressure meas. min: + 10°C
Ambient temperature pressure meas. max: + 40°C
Diaphragm seal, flange type, flush diaphragm
Specifications according to data sheet: DS 99.27
Diaphragm seal: Model 990.27
Diaphragm seal: Model 990.27
Process connection standard: following ASME B16.5
Process connection: 1 1/2"
Nominal pressure rating: Class 300
Sealing face: RF 125...250 AA
Upper body material / main body material: Stainless steel 1.4404 (316L); UNS S31603
Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603
Sealing face material: Stainless steel 1.4404 (316L); UNS S31603

Label: WIKA standard without / with Tag-number

© 2023 - WIKA Instruments s.a.r.l.