Specifications

Eaton 260182



Catalog Number: 260182

Eaton Moeller series NZM - Molded Case Circuit Breaker. Door coupling rotary handle, red-yellow for emergency switching off, size 3

General specifications

Product Name
Eaton Moeller series NZM operating element

Catalog Number
260182

EAN
4015082601829

Product Length/Depth
100 mm

Product Height
230 mm

Product Width
120 mm

Product Weight
1.434 kg

Compliances
UL/CSA
IEC
RoHS conform

Certifications
IEC60947
CSA certified
UL (Category Control Number DIHS)
CSA (Class No. 1437-01)
CSA (File No. 22086)
CSA-C22.2 No. 5-09
UL listed
UL489
UL (File No. E140305)
CE marking

Powering Business Worldwide

Product specifications

Used with

NZM3(-4), PN3(-4), N(S)3(-4)

Type

Accessory
Door coupling rotary handle

Special features

Door coupling rotary handle
for operating the switch
through a closed control
panel door
External warning
plate/designation label can
be clipped on.
Complete including rotary
drive and coupling parts
Extension shaft additionally
required.

Features

Lockable
Red-yellow for emergency switching off

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to

Resources

Brochures

eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf

eaton-digital-nzm-brochure-br013003en-en-us.pdf

Catalogs

eaton-digital-nzm-catalog-ca013003en-en-us.pdf

Declarations of conformity

DA-DC-03_NZM3

Drawings

eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-006.eps

eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-004.eps

eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-003.eps

eaton-circuit-breaker-padlock-nzm-rotary-handle-dimensions.eps

eaton-circuit-breaker-door-nzm-rotary-handle-3d-drawing-005.eps

Installation instructions

IL01208007Z

Installation videos

Introduction of the new digital circuit breaker NZM

The new digital NZM Range

mCAD model

DA-CS-nzm3_xtvd

DA-CD-nzm3_xtvd

Technical data sheets

eaton-nzm-technical-information-sheet

normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Color

Red

Fitted with:

Padlock

Frame

NZM3

Suitable for

Switch disconnector

Power circuit breaker

Emergency stop

Cover/door type

Door interlock not defeated in the locked OFF position.

Door interlock can be modified in the unlocked ON position

Door interlock can be modified such that it can be defeated from the outside using a screwdriver

Door can be opened in OFF

Lock number

Double lockable

Locking facility

Lockable on the handle on the switch using up to 3 padlocks

With door interlock

Degree of protection / NEMA enclosure type

IP66

4X. 12

Powering Business Worldwide

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia