DATASHEET - SL4-FL24-B-M

LED multistrobe light, blue 24V

Part no.	**SL4-FL24-B-M**
	171373
EL Number (Norway)	**4137608**

Product name	Eaton Moeller® series SL4 Multi-strobe light module
Part no.	SL4-FL24-B-M
EAN	4015081679034
Product Length/Depth	43 millimetre
Product height	75 millimetre
Product width	43 millimetre
Product weight	0.042 kilogram
Certifications	CSA-C22.2 No. 94-91 UL File No.: E29184 UL CSA-C22.2 No. 14-10 UL 508 Certified by UL for use in Canada UL Category Control No.: NKCR IEC/EN 60529 CSA Class No.: NKCR7 UL report applies to both US and Canada IEC/EN 60947-5-1 CE
Product Tradename	SL4
Product Type	Multi-strobe light module
Product Sub Type	None
Color	Blue
Enclosure color	Black
Features	Various strobe sequences
Functions	Flash light
Light modules	LED
Number of modules	Max. 10 (with base for mounting on both sides) Max. 5 (with standard base)
Connection to SmartWire-DT	No
Current consumption	0.048 - 0.068 A, at 24 V AC/DC
Degree of protection	IP66 NEMA 13
Flashing frequency	1 - 2.6 Hz
Lifespan, electrical	100,000 h
Light type	Multistrobe light
Material	Enclosure: Polycarbonate (PC) Cap: Polycarbonate (PC)
Mounting position	As required
Overvoltage category	III
Pollution degree	3
Product Category	SL signal towers
Radiation angle	360 °
Rated impulse withstand voltage (Uimp)	4000 V AC
Shock resistance	15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27
Type	LED for effective signaling effect Multi-strobe light module
Voltage type	AC/DC
Ambient operating temperature - min	-30 °C
Ambient operating temperature - max	60 °C

Climatic proofing			Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Leakage current			0.003 A
Rated insulation voltage (Ui)			250 V
Rated operational voltage (Ue) at AC - min			24 V
Rated operational voltage (Ue) at AC - max			24 V
Rated operational voltage (Ue) at DC - min			24 V
Rated operational voltage (Ue) at DC - max			24 V

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Optical module for signal tower (EC000232)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Optical module for signal tower (ecl@ss10.0.1-27-37-12-20 [AKF038014])

Function			Flash light
Colour			Blue
Outer diameter		mm	43
Operating voltage at AC 50 Hz		V	24 - 24
Operating voltage at AC 60 Hz		V	24 - 24
Operating voltage at DC		V	24 - 24
Voltage type			AC/DC
Lamp type			LED
Colour housing			Black
Degree of protection (IP)			IP66
Degree of protection (NEMA)			13

© 04/2023 by Eaton Industries GmbH