Specifications

Eaton 125486

Catalog Number: 125486

Eaton SPX Variable frequency drive, 400 V AC, 3-phase, 900 kW, IP00, OLED display, FR14



General specifications

Product Name
Eaton SPX variable frequency drive

Catalog Number
125486

EAN
4015081230921

Product Length/Depth
105.5 mm

Product Height
56.6 mm

Product Width
141.6 mm

Product Weight
872 kg

Certifications
CUL
CSA-C22.2 No. 14
IEC/EN61800-3
UL
DNV
UL 508C
IEC/EN 61800-3
Specification for general requirements:
IEC/EN 61800-2
CE
CSA Class No.: 3211-06
UL File No.: E134360
UL report applies to both US and Canada
Certified by UL for use in Canada
IEC/EN61800-5
UL Category Control No.: NMMS, NMMS2, NMMS7. NMMS8
RoHS, ISO 9001
Safety: EN 61800-5-1: 2003
RCM

Powering Business Worldwide

General

Degree of protection

IP00

NEMA Other

Electromagnetic compatibility

1st and 2nd environments (according to EN 61800-3)

Fitted with:

IGBT inverter

Internal DC link

PC connection

OLED display

Control unit

Frame size

FR14

Functions

4-quadrant operation possible

Mounting position

Vertical

Product Category

Variable frequency drives

Protection

Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)

Radio interference class

C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.

Suitable for

Branch circuits, (UL/CSA)

Climatic environmental conditions

Altitude

Above 1000 m with 1 % performance reduction per 100 m

Max. 1000 m

Max. 3000 m

Ambient operating temperature - min

-10 °C

Ambient operating temperature - max

40 °C

Ambient operating temperature at 150% overload - min

-10 °C

Ambient operating temperature at 150% overload - max

40 °C

Ambient storage temperature - min

-40 °C

Climatic proofing

< 95 % relative humidity, no condensation, no corrosion, no dripping water

Main circuit

Mains voltage - min

380 V

Mains voltage - max

500 V

Operating mode

Sensorless vector control (SLV)

U/f control

Optional: Vector control with feedback (CLV)

Output frequency - min

0 Hz

Output frequency - max

320 Hz

Output voltage (U2)

400 V AC, 3-phase

480 V AC, 3-phase

500 V AC, 3-phase

Rated control supply voltage

10 V DC (Us, max. 10 mA)

Rated frequency - min

45 Hz

Rated frequency - max

66 Hz

Rated operational current (Ie) at 110% overload

1770 A

Rated operational current (Ie) at 150% overload

1600 A

Rated operational power at 380/400 V, 50 Hz, 3-phase

900 kW

Rated operational power at 380/400 V, 50 Hz, 3-phase, 110% overload

1000 kW

Rated operational voltage

500 V AC, 3-phase

480 V AC, 3-phase

400 V AC, 3-phase

Resolution

0.01 Hz (Frequency resolution, setpoint value)

Supply frequency

50/60 Hz

Switching frequency

3.6 kHz, 1 - 6 kHz adjustable, fPWM, Power section, Main circuit

System configuration type

AC supply systems with earthed center point

Voltage rating - max

480 VAC

Motor rating

Assigned motor power at 460/480 V, 60 Hz, 3-phase

1200 HP

Assigned motor power at 460/480 V, 60 Hz, 3-phase, 110 % overload

1600 HP

Control circuit

Number of inputs (analog)

2

Number of inputs (digital)

6

Number of outputs (analog)

1

Number of outputs (digital)

1

Number of relay outputs

2 (parameterizable, N/O, 8 A (24 V DC) / 8 A (250 V AC) / 0,4 A (125 V DC))

Rated control voltage (Uc)

24 V DC (external, max. 250 mA)

Communication

Communication interface

CANopen®, optional

Modbus-TCP, optional

PROFIBUS-DP

LonWorks, optional

BACnet/IP, optional

DeviceNet, optional

BACnet MS/TP, optional

EtherCAT, optional

Ethernet IP, optional

Modbus-RTU, optional

PROFINET, optional

Connection to SmartWire-DT

No

Protocol

CAN

DeviceNet

PROFIBUS

TCP/IP

Data-Highway

LON

Other bus systems

Design verification

Equipment heat dissipation, current-dependent Pvid

22500 W

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

0 W

Rated operational current for specified heat dissipation (In)

1600 A

Static heat dissipation, non-current-dependent Pvs

0 W

Heat dissipation details

Operation (with 150 % overload)

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

Application notes

Electromagnetic compatibility (EMC)

SPI - Variable frequency drives with a common DC bus

Connecting drives to generator supplies

Catalogs

Product Range Catalog Drives Engineering

Declarations of conformity

DA-DC-00004869.pdf

DA-DC-00004868.pdf

Drawings

eaton-frequency-inverter-spx-dimensions-009.eps

eaton-frequency-inverter-spx-dimensions-006.eps

eaton-frequency-inverter-spx-dimensions-008.eps

eaton-frequency-inverter-spx-dimensions-004.eps

eaton-frequency-inverter-spx-dimensions-005.eps

Installation instructions

IL04020008Z

Multimedia

How does a VFD work to save energy and money?

Eaton variable frequency drives - Demand more innovation

Eaton variable frequency drives - Demand more than good enough

Eaton variable frequency drives - Demand more expertise

Product notifications

eaton-drives-ecodesign-directive-mz040046en-en.pdf

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.