# Product data sheet
## Characteristics

# ZCKY14
limit switch lever ZCKY - steel roller lever ball bearing mounted - -40..120 °C



## Main

| | |
|---|---|
| Range of product | OsiSense XC |
| Series name | Standard format |
| Product or component type | Limit switch lever |
| Device short name | ZCKY |
| Product compatibility | XCKJ |
| Associated head | ZCKE05 |
| Movement of operating head | Rotary |
| Type of operator | Roller lever spring return metal (ball bearing mounted) |
| Type of approach | Lateral approach |

## Complementary

| | |
|---|---|
| Switch actuation | By 30° cam |
| Positive opening | With |

## Environment

| | |
|---|---|
| Ambient air temperature for operation | 10...120 °C for high temperature<br>-40...70 °C for low temperature<br>-25...70 °C for standard environment |
| Ambient air temperature for storage | -40...70 °C for low temperature<br>10...120 °C for high temperature<br>-40...70 °C for standard environment |
| Environmental characteristic | High temperature<br>Low temperature<br>Standard environment |

## Offer Sustainability

| | |
|---|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0905 - Schneider Electric declaration of conformity |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Schneider Electric declaration of conformity

| | |
|---|---|
| REACh | Reference not containing SVHC above the threshold<br>Reference not containing SVHC above the threshold |
| Product end of life instructions | Need no specific recycling operations |

## Contractual warranty

| | |
|---|---|
| Warranty period | 18 months |