
69001-866 CONNECTOR TYPE H, EN 60603, DIN 41612, MALE, 15 CONTACTS, FASTON 6.3 MM







KEY FEATURES

- Requirement class 2 as per EN 60603 (DIN 41642)
- Separate Coding
- Coding on the connector

PRODUCT ATTRIBUTES

- Product Type: Connector
- Type: Male Connectors
- Works With: Front Panels
- Number of Contacts: 15
- Contact Material: Silver Plated
- Connector Pitch: 5.08 mm
- Min Creepage Distance, Contact-Contact: 8 mm
- Min Air Gap, Contact-Contact: 4.5 mm
- Max Current @ 20°C: 6 A
- Max Contact Resistance: 8 mO
- Max Insertion and Withdrawal Force: 90 N
- Test Voltage (Ueff), Contact-Contact: 1.55 kV
- Test Voltage (Ueff), Contact-Earth: 2.5 kV
- Row Assignment: Z; D

ADDITIONAL PRODUCT DETAILS

Male / Female DIN connector form H. Requirement class 2 as per EN 60603 (DIN 41642).

CERTIFICATIONS





North America
All locations
+1.763.422.2661
Chat with us:
schroff.nvent.com

Europe
Straubenhardt, Germany
+49.7082.794.0
Betschdorf, France
+33.3.88.90.64.90
Warsaw, Poland
+48.22.209.98.35
Assago, Italy
+39.02.932.7141
Chat with us:
schroff.nvent.com

Asia
Shanghai, China
+86.21.2412.6943
Qingdao, China
+86.532.8771.6101
Singapore
+65.6768.5800
Shin-Yokohama, Japan
+81.45.476.0271
Chat with us:
schroff.nvent.com

Middle East & India
Dubai, United Arab Emirates
+971.4.378.1700
Bangalore, India
+91.80.6715.2001
Istanbul, Turkey
+90.216.250.7374
Chat with us:
schroff.nvent.com

nVent

Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.