Paint spray guns

Suction-feed spray gun for industrial spray painting



Technical characteristics


Construction: Body : Aluminium
Needle : Stainless steel

Applications: Automotive and industrial sectors

Highlight: Three types of adjustment (width of stream, paint flow rate and air flow rate)

BSPP male thread: G 1/4

Blue anodised aluminium body
1-litre anodised aluminium cup
Working pressure: 3,5 bar to 5 bar
Air consumption: 280 to 360 l/min under 3 bar
Weight: 1,1 kg
G 1/4 M connection
G 3/8 cup connection thread



A (mm)	B (mm)	Nozzle Ø (mm)	Parts Numbers
160	300	1	**CAR S021**
160	300	1.6	**CAR S02**
160	300	1.8	**CAR S022**
160	300	2	**CAR S023**

PREVOST UK - G, Tower Business Park, Commercial Rd, Darwen BB3 0FJ - United Kingdom
Tel. : (+44) 0844 800 2788 - Fax : (+44) 0844 800 2789 - E-mail : sales@prevost-ltd.co.uk - www.prevost.eu International = PREVOST SAS - - C.S. 90208 - 74942 ANNECY-LE-VIEUX CEDEX - France Tel. : +33 (4)50 64 04 45 - Fax : +33 (0)4 50 64 00 10 - E-mail : sales@prevost.eu- www.prevost.eu

This document is non-contractual. PREVOST reserves the right to modify the features of its range without prior notice.