Cable Guard KT14

PVC Cable Guard for rewireable connectors





Description

- 1 Function:

- Press-Fit Version
- bend protection for cable

Weblinks

pdf-datasheet, html-datasheet, General Product Information, Approvals, CE declaration of conformity, RoHS, CHINA-RoHS, REACH, Mating Connectors, e-Shop, SCHURTER-Stock-Check, Distributor-Stock-Check, CAD-Drawings, Accessories, Detailed request for product

All Variants

Suitable for	Color	For cables with outer diameter of	Length [mm]	Order Number	
1651, 4013, 4020, 4021, 4022, 8101, 8111, 9013	white	8.7 mm	39.4 mm	4311.0053	
0104, 0104U, 0106	white	10 mm	39 mm	4311.0063	
0104, 0104U, 0106	white	8 mm	38 mm	4311.0064	
4012	white	8 mm	37.5 mm	4311.0067	
1651, 4013, 4020, 4021, 4022, 8101, 8111, 9013	white	10 mm	39 mm	4311.0068	
0104, 0104U, 0106	black	8 - 10 mm	40.3 mm	4311.9301	
0104, 0104U, 0106	grey	8 - 10 mm	40.3 mm	4311.9302	
1651, 4013, 4020, 4021, 4022, 8101, 8111, 9013	black	8.7 - 10 mm	40.3 mm	4311.9305	
1651, 4013, 4020, 4021, 4022, 8101, 8111, 9013	grey	8.7 - 10 mm	40.3 mm	4311.9306	
4012	black	8 - 10 mm	36.7 mm	4311.9307	
1251	black	6.5 mm	30 mm	4311.9309	
0101, 0102, 0104, 0104U, 0106, 0112, 4771, 4772	black	8 mm	38 mm	4311.9310	
0101, 0102, 0112, 4771, 4772	black	10 mm	40 mm	4311.9313	
0104, 0104U, 0106	grey	10 mm	39 mm	4311.9315	
1651, 4013, 4020, 4021, 4022, 8101, 8111, 9013	black	8.7 mm	39.4 mm	4311.9316	
1651, 4013, 4020, 4021, 4022, 8101, 8111, 9013	grey	8.7 mm	39.4 mm	4311.9317	
1651, 4013, 4020, 4021, 4022, 8101, 8111, 9013	black	10 mm	39 mm	4311.9318	
1651, 4013, 4020, 4021, 4022, 8101, 8111, 9013	grey	10 mm	39 mm	4311.9319	
4012	black	8 mm	37.5 mm	4311.9320	
4012	grey	8 mm	37.5 mm	4311.9321	
4012	black	10 mm	37 mm	4311.9322	
1251	white	6.5 mm	30 mm	4311.9324	

Packaging unit 100 Pcs

03.03.2015

The specifications, descriptions and illustrations indicated in this document are based on current information. All content is subject to modifications and amendments. Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability and test each product selected for their own applications.