# DATASHEET - IZMX-MIL3133C-W16-1

**Mechanical interlock, TYPE 2, 31, 33, bowden cables, W**

| | |
|---|---|
| **Part no.** | **IZMX-MIL3133C-W16-1** |
| | **184213** |
| **EL Number (Norway)** | **4398556** |

| | |
|---|---|
| **General specifications** | |
| Product name | Eaton Moeller series IZMX/INX mechanical interlock |
| Part no. | IZMX-MIL3133C-W16-1 |
| EAN | 4015081783793 |
| Product Length/Depth | 457.2 millimetre |
| Product height | 203.2 millimetre |
| Product width | 457.2 millimetre |
| Product weight | 1.149 kilogram |
| Compliances | RoHS conform |
| Product Tradename | IZMX/INX |
| Product Type | Accessories |
| Product Sub Type | Mechanical interlock |
| **Delivery program** | |
| Type | Accessory |
| Special features | For 3 circuit breakers -three incoming units (A, B, C), normal or emergency network. Only one of the three switches can be switched on at any one time. Three cable kits are required in addition.<br>Type 31 + 33 |
| Used with | IZMX16…W<br>INX16…W |
| **Technical Data - Mechanical** | |
| Mounting Method | Withdrawable |
| Number of contacts (normally closed contacts) | 0 |
| Number of contacts (normally open contacts) | 0 |
| **Design verification as per IEC/EN 61439 - technical data** | |
| Ambient operating temperature - min | -25 °C |
| Ambient operating temperature - max | 70 °C |
| **Additional information** | |
| Accessory/spare part type | Withdrawable units |

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Mechanic interlock for switch (EC001044)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Mechanic interlock for switch (ecl@ss13-27-37-13-03 [AKN341018])

| | |
|---|---|
| Auxiliary contacts, extendable | No |
| Number of contacts as normally closed contact | 0 |
| Number of contacts as normally open contact | 0 |


© 04/2023 by Eaton Industries GmbH