*Date: 12/04/2023*

# MW-XXDN - 0...10 bar - Adaptor G 1/2 A-M - 1/2 -14 NPT-F

## Mechanical Pressure Switch for the Process Industry

Item number: 48633220

Quantity: 1 pcs.

Order code: MW-XXDN-BBJSB-4AMZZZZZZZZZZZZZZZZZZZZZZ ZCK2AW

Overview:
MW-XXDN - 0...10 bar - Adaptor G 1/2 A-M - 1/2 -14 NPT-F
Diaphragm pressure switch, Stainless steel case
measuring elements and wetted materials: Diaphragm AISI 316, 304, Inconel or Hastelloy (Piston AISI 316)/ Process Connection AISI 316L
Contact version: 2 x SPDT or 1 x DPDT silver contact
setting range: 0...10 bar
Standard, working range = 0...10 bar, proof pressure 20 bar
Process connection: Adaptor G 1/2 A-M
Electrical connection: 1/2 -14 NPT-F
Enclosure with plate for wall or direct mounting
Ingress Protection: IP66
Diaphragm: Stainless steel AISI 304/O-Ring: FPM/Connection: Stainless steel AISI 316L
Brand: WIKA Instruments Italia
Specifications according to data sheet: PV 31.10
Repeatability of set point: ≤ 1% of span

Set point definition: Set Point not defined

Details:
Mechanical Pressure Switch for the Process Industry
Diaphragm element, 316L enclosure
Model MW
Specifications according to data sheet: PV 31.10
setting range: 0...10 bar
working range: Standard, working range = 0...10 bar, proof pressure 20 bar
number of switches: 2xSPDT
contact type: silver contact
set point definition: Set Point not defined
electrical connection: 1/2 -14 NPT-F
measuring elements and wetted materials: Diaphragm Stainless Steel or Inconel / Process Connection Stainless Steel
process connection: Adaptor G 1/2 A-M
Mounting: Enclosure with plate for wall or direct mounting
Ingress Protection: IP66
O-Ring: FPM
Diaphragm pressure switch, Stainless steel case
Model MW
Specifications according to data sheet: PV 31.10

*© 2023 - WIKA Instruments s.a.r.l.*

Repeatability of set point: ≤ 1% of span
Contact version: 2 x SPDT or 1 x DPDT silver contact
setting range: 0...10 bar
working range: Standard, working range = 0...10 bar, proof pressure 20 bar
Set Point not defined
Unit: bar
Process connection: Adaptor G 1/2 A-M
Electrical connection: 1/2 -14 NPT-F
Enclosure with plate for wall or direct mounting
Brand: WIKA Instruments Italia
Ingress Protection: IP66
MW-XXDN
Diaphragm: Stainless steel AISI 304/O-Ring: FPM/Connection: Stainless steel AISI 316L

© 2023 - WIKA Instruments s.a.r.l.