PRODUCT-DETAILS

S201M-K40UC

S201M-K40UC Miniature Circuit Breaker - 1P - K - 40 A



General Information

Extended Product Type	S201M-K40UC
Product ID	2CDS271061R0557
EAN	4013614431074
Catalog Description	S201M-K40UC Miniature Circuit Breaker - 1P - K - 40 A
Long Description	The miniature circuit breaker S 200 M UC extends the established ABB System pro M compact® product range with an MCB for DC and AC applications. The S 200 M UC impresses with its performance range and the accordingly large amount of approvals. Its high inbuilt short circuit breaking capacity across the entire model line, its flexible AC and DC application and its approval and compliance in accordance with all major international and local standards make it truly unique. All current System pro M compact® accessories can be combined easily with the new model line. Whether warehousing or project engineering, planning, installing or maintaining your equipment, the S 200 M UC is a simple and flexible solution.

Technical

Standards	CSA 22.2 No. 235 IEC/EN 60947-2 UL 1077
Tripping Characteristic	K
Rated Operational Voltage	acc. to IEC 60898-1 230 V AC acc. to IEC 60898-1 220 V

© 2024 ABB. All rights reserved.

	acc. to IEC 60947-2 253 V AC acc. to IEC 60947-2 220 V DC
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 440 V
Rated Impulse Withstand Voltage (U_{imp})	4 kV at 2000 m 5 kV at Sea Level 6.2 kV
Input Voltage Type	AC/DC
Rated Current (I_n)	40 A
Rated Short-Circuit Capacity	(AC) 10 kA (230 V AC) 10 kA (230 V) 10 kA (400 V) 10 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(110 V DC) 20 kA (220 V DC) 10 kA (230 V AC) 10 kA (253 V AC) 10 kA (230 V) 10 kA
Rated Conditional Short-Circuit Current (I_{nc})	(230 V) 10 kA
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(110 V DC) 10 kA (230 V AC) 10 kA
Rated Frequency (f)	50 / 60 Hz DC
Power Loss	3.76 W at Rated Operating Conditions per Pole 3.76 W
Power Supply Connection	Please Note Polarity of Device
Contact Position Indication	Red ON / Green OFF
Energy Limiting Class	3
Mechanical Endurance	20000 cycle
Number of Protected Poles	1
Number of Poles	1
Overvoltage Category	III
Tightening Torque	2.8 N·m
Screw Terminal Type	Failsafe Bi-directional Cylinder-lift Terminal
Actuator Marking	I / O
Actuator Material	Insulation Group II, Black, Sealable
Housing Material	Insulation Group I, RAL 7035
Options Provided	Universal current
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Mounting Position	any
Recommended Screw Driver	Pozidriv 2
Accessories Available	Yes
Remarks	Please note polarity of device
Connecting Capacity	Busbar 10 / 10 mm² Flexible with Ferrule 0.75 ... 25 mm² Flexible 0.75 ... 25 mm² Flexible 0.75 ... 25 mm² Rigid 0.75 ... 35 mm² Stranded 0.75 ... 35 mm²
Installation Size	acc. to DIN 43880 1
Terminal Type	Screw Terminals

Material Compliance

RoHS Information	2CDK400583D2704
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20110608
REACH Declaration	9AKK108468A9644

© 2024 ABB. All rights reserved.

REACH Information	True - contains substances > 0.1 mass percentage
REACH Date	20231212
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
SCIP	cec6beff-be12-4313-bcef-0d0cbaa3ae87 Germany (DE)

Environmental

Ambient Air Temperature	Operation -25 ... +55 °C Storage -40 ... +70 °C
Degree of Protection	IP20 Enclosure with Cover IP40
Pollution Degree	3
Environmental Conditions	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
Resistance to Vibrations	20 Cycles with Load 0.8 In: 5g 5 ... 150 ... 5 Hz
Resistance to Shock acc. to IEC 60068-2-27	25g 2 shocks 13 ms
Environmental Information	2CDK400030D201

Technical UL/CSA

Maximum Operating Voltage UL/CSA	250 V DC 480Y / 277 V AC
Interrupting Rating acc. to UL1077	(110 V DC) 10 kA (220 V AC) 10 kA (250 V DC) 10 kA (253 V AC) 6 kA (480Y / 277 V AC) 10 kA
Connecting Capacity UL/CSA	Busbar 14-8 AWG Conductor 14-4 AWG
Tightening Torque UL/CSA	25 in·lb

Dimensions

Width in Number of Modular Spacings	1.0
Product Net Width	17.5 mm
Product Net Height	85 mm
Product Net Depth / Length	69 mm
Product Net Weight	0.125 kg
Pole Net Weight	0.125 kg
Built-In Depth (t_2)	69 mm

Ordering

Package Level 1 Units	carton 10 piece
Package Level 1 Gross Weight	1.3 kg
E-Number (Finland)	3210291

Certificates and Declarations

Declaration of Conformity - CE	2CDK400583D2704
Certification Agency	CSA

© 2024 ABB. All rights reserved.

EN
IEC
UL

Installation

Instructions and Manuals	2CDS207104P0002

Popular Downloads

Data Sheet, Technical Information	2CDC002142D0207

Classifications

ETIM 8	EC000042 - Miniature circuit breaker (MCB)
ETIM 9	EC000042 - Miniature circuit breaker (MCB)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	8536 20 10
UNSPSC	39121603
eClass	V11.0 : 27141901
IDEA Granular Category Code (IGCC)	4899 >> Miniature circuit breaker (MCB) screw-in model
Object Classification Code	F

Accessories

© 2024 ABB. All rights reserved.

Identifier	Description	Type	Quantity	Unit Of Measure
2CDS200922R0001	S2C-S/H6R Signal / Auxiliary Contact	S2C-S/H6R	1	piece
2CDS200912R0001	S2C-H6R Auxiliary Contact	S2C-H6R	1	piece
2CDS200970R0031	S2C-H01 Auxiliary Contact	S2C-H01	1	piece
2CDS200970R0032	S2C-H10 Auxiliary Contact	S2C-H10	1	piece
2CDS200936R0001	S2C-H11L Auxiliary Contact	S2C-H11L	1	piece
2CDS200936R0002	S2C-H20L Auxiliary Contact	S2C-H20L	1	piece
2CDS200936R0003	S2C-H02L Auxiliary Contact	S2C-H02L	1	piece
2CDS200946R0001	S2C-H6-11R Auxiliary Contact	S2C-H6-11R	1	piece
2CDS200946R0002	S2C-H6-20R Auxiliary Contact	S2C-H6-20R	1	piece
2CDS200946R0003	S2C-H6-02R Auxiliary Contact	S2C-H6-02R	1	piece
2CDS200909R0001	S2C-A1 Shunt Trip	S2C-A1	1	piece
2CDS200909R0002	S2C-A2 Shunt Trip	S2C-A2	1	piece
2CSS200911R0001	S2C-UA 12 DC Undervoltage Release	S2C-UA 12 DC	1	piece
2CSS200911R0002	S2C-UA 24 AC Undervoltage Release	S2C-UA 24 AC	1	piece
2CSS200911R0003	S2C-UA 48 AC Undervoltage Release	S2C-UA 48 AC	1	piece
2CSS200911R0004	S2C-UA 110 AC Undervoltage Release	S2C-UA 110 AC	1	piece
2CSS200911R0005	S2C-UA 230 AC Undervoltage Release	S2C-UA 230 AC	1	piece
2CSS200911R0006	S2C-UA 400 AC Undervoltage Release	S2C-UA 400 AC	1	piece
2CSS200911R0007	S2C-UA 24 DC Undervoltage Release	S2C-UA 24 DC	1	piece
2CSS200911R0008	S2C-UA 48 DC Undervoltage Release	S2C-UA 48 DC	1	piece
2CSS200911R0009	S2C-UA 110 DC Undervoltage Release	S2C-UA 110 DC	1	piece
2CSS200911R0010	S2C-UA 230 DC Undervoltage Release	S2C-UA 230 DC	1	piece
GHS2001901R0003	S2C-DH Mechanical Accessories	S2C-DH	1	piece
2CSS200998R0001	S2C-BP Mechanical tripping device	S2C-BP	1	piece
2CSS200999R0001	S2C-EST Plug-in base	S2C-EST	1	piece
2CDS200918R0001	S2C-NT Hand Operated Neutral	S2C-NT	1	piece
2CCA880100R0001	CMS-100PS Sensor	CMS-100PS	1	piece
2CCA880101R0001	CMS-101PS Sensor	CMS-101PS	1	piece
2CCA880102R0001	CMS-102PS Sensor	CMS-102PS	1	piece

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs

© 2024 ABB. All rights reserved.





© 2024 ABB. All rights reserved.