PRODUCT-DETAILS

# OS200B22BBN2P

## OS200B22BBN2P SPECIAL CONNECTED SWITCH FUSE



### General Information

| | |
|---|---|
| Extended Product Type | OS200B22BBN2P |
| Product ID | 1SCA102130R1001 |
| EAN | 6417019369167 |
| Catalog Description | OS200B22BBN2P SPECIAL CONNECTED SWITCH FUSE |
| Long Description | Switch Fuses,Front Operated,4-pole,22 (Between the Poles),British Standard,B1-B2,Handle and shaft included,Switched - With Solid Link |

### Ordering

| | |
|---|---|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85365080 |
| Country of Origin | Finland (FI) |

### Popular Downloads

| | |
|---|---|
| Data Sheet, Technical Information | 1SCC311091D0201 |
| Instructions and Manuals | 1SCC311012M0219 |

### Dimensions

| | |
|---|---|
| Product Net Width | 219 mm |

| | |
|---|---|
| Product Net Height | 145 mm |
| Product Net Depth / Length | 179 mm |
| Product Net Weight | 4.25 kg<br>9.37 lb |

## Technical

| | |
|---|---|
| Rated Operational Current AC-21A ($I_e$) | (500 V) 200 A<br>(690 V) 200 A |
| Rated Operational Current AC-22A ($I_e$) | (380 ... 415 V) 200 A<br>(500 V) 200 A<br>(690 V) 200 A |
| Rated Operational Current AC-23A ($I_e$) | (380 ... 415 V) 200 A<br>(500 V) 200 A<br>(690 V) 200 A |
| Rated Operational Power AC-23A ($P_e$) | (220 ... 240 V) 60 kW<br>(400 V) 110 kW<br>(415 V) 110 kW<br>(500 V) 132 kW<br>(690 V) 200 kW |
| Conventional Free-air Thermal Current ($I_{th}$) | q = 40 °C 200 A |
| Conventional Thermal Current ($I_{the}$) | Fully Enclosed 200 A |
| Rated Impulse Withstand Voltage ($U_{imp}$) | 12 kV |
| Rated Insulation Voltage ($U_i$) | 1000 V |
| Rated Operational Voltage | 500 V |
| Rated Short-time Withstand Current ($I_{cw}$) | for 1 s 8 kiloampere rms |
| Rated Conditional Short-Circuit Current ($I_{nc}$) | (690 V) 80 kA |
| Power Loss | at Rated Operating Conditions per Pole 17 W |
| Pollution Degree | 3 |
| Handle Type | Pistol handle and shaft included |
| Fourth Pole Position | Right Side |
| Fourth Pole Type | Switched - With Solid Link |
| Switches Operating Mechanism | 22 (Between the Poles) |
| Position of Line Terminals | Back In - Back Out |
| Fuse Size | B1-B2 |
| Fuse System | British Standard |
| Operating Mode | Front Operated |
| Standards | IEC 60947-3 |
| Mounting Type | Base mounting |
| Number of Poles | 4 |
| Terminal Type | Lug terminals |
| Terminal Width | 20 mm |
| Tightening Torque | 15 ... 22 N·m |
| Fuse Type | BS |

## Environmental

| | |
|---|---|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

## Certificates and Declarations (Document Number)

| | |
|---|---|
| Declaration of Conformity - CE | 1SCC311119D2702 |
| EAC Certificate | EAC OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSM_.pdf |
| Instructions and Manuals | 1SCC311012M0219 |
| RoHS Information | 1SCC311119D2702 |

## Container Information

| | |
|---|---|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 255 mm<br>10.04 in |
| Package Level 1 Depth / Length | 460 mm<br>18.11 in |
| Package Level 1 Height | 253 mm<br>9.96 in |
| Package Level 1 Gross Weight | 5 kg<br>11.02 lb |
| Package Level 1 EAN | 6417019369167 |

## Classifications

| | |
|---|---|
| Object Classification Code | Q |
| ETIM 4 | EC001040 - Fuse switch disconnector |
| ETIM 5 | EC001040 - Fuse switch disconnector |
| ETIM 6 | EC001040 - Fuse switch disconnector |
| ETIM 7 | EC001040 - Fuse switch disconnector |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

## Categories

Low Voltage Products and Systems → Switches → Switch Fuses

