metal quick acting couplers
Flow : 2200 Nl/min (78 cfm)
Passage : 12 mm

series «midi»
single shut-off
straight through



Series «midi» couplers are adapted for all applications working with water and compressed air.

The wide variety of probes allows these couplers many options.

0172 female body, BSP parallel



C		kg
G3/8	0172 12 17	0,160
G1/2	0172 12 21	0,145

with shut-off

2272 female body, BSP parallel



C		kg
G1/2	2272 12 21	0,070
G3/4	2272 12 27	0,078
G1“	2272 12 34	0,086

straight through

2511 body with barbed fitting



ØD	DN		kg
12	9	2511 12 12	0,152
15	12	2511 12 15	0,152
19	16	2511 12 19	0,162

with shut-off

2297 body with barbed fitting



ØD	DN		kg
12	9	2297 12 12	0,077
15	12	2297 12 15	0,079
19	16	2297 12 19	0,094

straight through

2294 male thread, BSP parallel



C	DN		kg
G3/8	12	2294 12 17	0,032
G1/2	12	2294 12 21	0,044
G3/4	12	2294 12 27	0,065
G1“	12	2294 12 34	0,071

0196 female thread, BSP parallel



C		kg
G1/4	0196 12 13	0,027
G3/8	0196 12 17	0,034
G1/2	0196 12 21	0,051

2296 female thread, BSP parallel



C	DN		kg
G1/2	12	2296 12 21	0,029
G3/4	12	2296 12 27	0,060
G1“	12	2296 12 34	0,058

0195 probe for flexible tube



ØD		kg
7	0195 07 00	0,027
10	0195 10 00	0,026
13	0195 13 00	0,031
16	0195 16 00	0,048

2295 probe for flexible tube



ØD	DN		kg
12	9	2295 12 12	0,026
15	12	2295 12 15	0,032
19	12	2295 12 19	0,053

maximum working pressure = 20 bar

0172 and 2511 couplers incorporate a shut-off valve which stops fluid flow when the probe is removed.