DATASHEET - IKA-1/8-OT



IKA standard distribution board, IP65 without clamps

Part no.	**IKA-1/8-OT**
	174205
EL Number (Norway)	**1702939**

General specifications

Product name	Eaton xComfort IKA standard series
Part no.	IKA-1/8-OT
EAN	4015081706679
Product Length/Depth	115 millimetre
Product height	231 millimetre
Product width	238 millimetre
Product weight	0.84 kilogram
Compliances	RoHS conform
Certifications	IEC/EN 60670-24 EN 62208
Product Tradename	xComfort IKA
Product Type	Standard series
Product Sub Type	None

Delivery program

Type	Basic device IKA standard distribution board Installation distribution board
Application	Indoor (installation site)
Color	Light gray (RAL 7035) Gray

Technical Data - Electrical

Voltage rating at AC	415 V AC
Frequency rating of contacts	50 Hz

Technical Data - Mechanical

Closure type	Other
Enclosure material	Plastic
Width in number of modular spacings	8
Mounting method	Surface mounted (plaster) Surface mounting DIN-rail
Material	ABS (plastic)
Degree of protection	IK08 (impact resistance) IP65
Number of module space units per row	8
Number of rows	1
Terminal type	Without terminals
Built-in depth	70 mm
Built-in height	0 mm
Built-in width	0 mm
Internal depth	60 mm
Cover/door color	Transparent
Cover/door model	With notch
Cover/door type	Single Door
Module rack type	Single-rail
Protective shrouding material	Plastic

Temperature-rise verification as per IEC 60890

Heat diss. ambient 35°C delta T:20°C wall mount individ. encl. top (IEC 60890)	14 W
Heat diss. ambient 35°C delta T:35°C wall mount individ. encl. top (IEC 60890)	29 W

Design verification as per IEC/EN 61439 - technical data

Ambient operating temperature details		-25 °C - 40 °C

Design verification as per IEC/EN 61439

10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		650 °C; meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Not relevant to indoor installations.
10.2.5 Lifting		Does not apply to enclosures without lifting aids.
10.2.6 Mechanical impact		IK08
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		IP65
10.4 Clearances and creepage distances		Is the panel builder's responsibility.
10.5 Protection against electric shock		Protection class 2, therefore not applicable.
10.6 Incorporation of switching devices and components		Is the panel builder's responsibility.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Ui = 1000 V AC
10.9.3 Impulse withstand voltage		3.3 kV
10.9.4 Testing of enclosures made of insulating material		Meets the product standard's requirements.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility.
10.13 Mechanical function		Meets the product standard's requirements.

Additional information

Fitted with:		Current circuit designation Device support rails Sealing caps Basic device Locking screws can be sealed
Functions		Basic device Extension possible
Protection class		II (totally insulated)
RAL-number		7035
Special features		IP65 Protection Class II Plastic enclosure gray (RAL 7035)
Used with		IKA standard distribution board Basic device Installation distribution board

Technical data ETIM 9.0

Distribution boards (EG000023) / Small distribution board (EC000214)

Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (including small distribution board) / Small distribution board (ecl@ss13-27-14-24-09 [ACN387016])

Mounting method			Surface mounted
Number of rows			1
Width in number of modular spacings			8
Type of covering			Door
Cover model			With notch
Type of door			Single
Transparent cover/door			Yes
Signal passing door			No
With lock			No
Type of closure			Other
Housing material			Plastic
Built-in depth		mm	70
Built-in height		mm	0
Built-in width		mm	0
Inner depth		mm	60
Earthing terminal block			No

Neutral terminal block			No
DIN-rail			Yes
With mounting plate			No
Extension possible			Yes
EMC-version			No
UV resistant			No
Colour			Grey
RAL-number			7035
Degree of protection (IP)			IP65
Height		mm	231
Width		mm	238
Depth		mm	115

© 04/2023 by Eaton Industries GmbH