Specifications

Eaton C22G8

Catalog Number: C22G8

Eaton Bussmann series low voltage 22 x 58 mm cylindrical/ferrule fuse, rated at 690 Volts AC, 8 Amps, 80 kA Breaking capacity, class gG/gL, without indicator, compatible with a CH22 Modular fuse holder



General specifications

Product Name
Eaton Bussmann series low voltage cylindrical fuse

Catalog Number
C22G8

EAN
5027590495554

UPC
051712667319

Product Length/Depth
58 mm

Product Height
22.2 mm

Product Width
22.2 mm

Product Weight
54.5 g

Compliances
CE Marked
GoST-R
RoHS Compliant

Certifications
IEC 60269

Powering Business Worldwide

Electrical data

Amperage Rating

8 A

Voltage rating

690 V

Voltage type

AC

Breaking capacity

80 kA

Utilization category

gG (cable protection/equipment protection)

Frequency rating - max

62 Hz

Compatible fuse holder

Suitable for

CH22 Modular fuse holder

Resources

Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

CA134002EN

Declarations of conformity

UKCA C08G, C08M, etc cylindrical fuselinks

CE C08G, C08M, etc cylindrical fuselinks

Technical data sheets

720115 Cylindrical fuses

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia