PRODUCT-DETAILS

SN201-C4

Miniature circuit breaker - SN201 - 1P+N - 4 A - C



General Information

Extended Product Type	SN201-C4
Product ID	2CSS255101R0044
EAN	8012542091554
Catalog Description	Miniature circuit breaker - SN201 - 1P+N - 4 A - C
Long Description	The SN201 series miniature circuit breaker is a 1P+N device in 1 module for the protection of circuits against overload and short circuit. Neutral is on the right

ABB EcoSolutions

ABB EcoSolutions	Yes
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 90.63 %
Sustainable Material Content in Packaging (wt. %)	Recycled Paper - 00 % Recycled Cardboard - 79 %
Extended Product Lifetime	Product Durability
End Of Life Disassembling	9AKK108469A7476

© 2024 ABB. All rights reserved.

Instructions	
Environmental Product Declaration - EPD	9AKK108469A9820

Technical

Standards	IEC/EN 60898-1
Tripping Characteristic	C
Rated Voltage (U_r)	230 V AC
Rated Operational Voltage	acc. to IEC 60898-1 230 V
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 500 V
Rated Impulse Withstand Voltage (U_{imp})	4 kV
Dielectric Test Voltage	2 kV
Primary Rated Impulse Withstand Voltage	4 kV
Input Voltage Type	AC
Rated Current (I_n)	4 A
Rated Short-Circuit Capacity	(230 V) 6 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(230 V) 10 kA
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(230 V AC) 6 kA
Rated Frequency (f)	50/60 Hz
Power Loss	2.4 W
Power Supply Connection	Arbitrary
Contact Position Indication	Red ON / Green OFF
Energy Limiting Class	3
Electrical Endurance	10000 cycle
Mechanical Endurance	20000 cycle
Number of Protected Poles	1
Number of Poles	1P+N
Number of Modular Spacings per DIN Rail	1
Overvoltage Category	III
Position of Neutral Terminals	Right
Tightening Torque	1.2 N·m
Accessory Type	Auxiliary contact Signal contact / auxiliary contact Shunt trip Undervoltage release
Actuator Type	Toggle - Insulation group IIIA, black, sealable in ON-OFF positions
Housing Type	Insulation group II, RAL 7035
Screw Terminal Type	Cage Terminal
Mounting Position	Any
Accessories Available	Yes
Connecting Capacity	Flexible 1 … 10 mm² Rigid 1 … 16 mm²

© 2024 ABB. All rights reserved.

Wire Stripping Length	11 mm
Terminal Type	Screw Terminals

Material Compliance

RoHS Information	9AKK106713A5572
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	20190722
REACH Information	No data - If REACH inform is not yet available for a certain product
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Temperature	-25...55 °C
Ambient Air Temperature	Operation -25 … 55 °C
Reference Ambient Air Temperature	30 °C
Degree of Protection	IP20
Pollution Degree	2
Environmental Conditions	28 cycles ;with 55 °C / 90-96 % ;and 25 °C / 95-100 %
Resistance to Vibrations	20 Cycles with Load 0.8 In: 5g or 0.35mm 5 … 150 … 5 Hz
Resistance to Shock acc. to IEC 60068-2-27	30g 2 shocks 13 ms
Environmental Information	refer to RoHS information

Dimensions

Width in Number of Modular Spacings	1
Product Net Width	18 mm
Product Net Height	85 mm
Product Net Depth / Length	69 mm
Product Net Weight	110 g
Built-In Depth (t_2)	69 mm

Ordering

Package Level 1 Units	box 6 piece
Package Level 1 Gross Weight	0.684 kg
E-Number (Finland)	3217751
E-Number (Norway)	1630651
E-Number (Sweden)	2100320

Certificates and Declarations

Declaration of	9AKK106713A5572

© 2024 ABB. All rights reserved.

Conformity - CE

Installation

Instructions and Manuals	No document needed

Popular Downloads

Data Sheet, Technical Information	2CSC400002D0209

Classifications

ETIM 8	EC000042 - Miniature circuit breaker (MCB)
ETIM 9	EC000042 - Miniature circuit breaker (MCB)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85362010
UNSPSC	39121603
eClass	V11.0 : 27141901
IDEA Granular Category Code (IGCC)	4899 >> Miniature circuit breaker (MCB) screw-in model
Object Classification Code	F

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CSS200924R0001	Signal Contact	SN201-S	1	piece
2CSS200923R0001	Interface module with auxiliary contact	SN201-IH	1	piece
2CDS200922R0001	Signal / Auxiliary Contact	S2C-S/H6R	1	piece
2CDS200912R0001	Auxiliary Contact	S2C-H6R	1	piece
2CSS200933R0011	Shunt trip	F2C-A1	1	piece
2CSS200933R0012	Shunt trip	F2C-A2	1	piece
2CSS200911R0001	Undervoltage Release	S2C-UA 12 DC	1	piece
2CSS200911R0002	Undervoltage Release	S2C-UA 24 AC	1	piece
2CSS200911R0003	Undervoltage Release	S2C-UA 48 AC	1	piece
2CSS200911R0004	Undervoltage Release	S2C-UA 110 AC	1	piece
2CSS200911R0005	Undervoltage Release	S2C-UA 230 AC	1	piece
2CSS200911R0006	Undervoltage Release	S2C-UA 400 AC	1	piece
2CSS200911R0007	Undervoltage Release	S2C-UA 24 DC	1	piece
2CSS200911R0008	Undervoltage Release	S2C-UA 48 DC	1	piece
2CSS200911R0009	Undervoltage Release	S2C-UA 110 DC	1	piece
2CSS200911R0010	Undervoltage Release	S2C-UA 230 DC	1	piece

© 2024 ABB. All rights reserved.

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs







ABB Eco Solutions™

© 2024 ABB. All rights reserved.