Specifications

Eaton 138381



Catalog Number: 138381

Eaton xEffect SASY 60i Enclosures Switch- & Controlgear Enclosure. Busbar support 4p, for flat busbars

General specifications

Product Name
Eaton xEffect SASY 60i busbar support

Catalog Number
138381

EAN
4015081351619

Product Length/Depth
51 mm

Product Height
245 mm

Product Width
20 mm

Product Weight
0.184 kg

Compliances
RoHS conform

Certifications
IEC/EN 60439-1, VDE 0660 Part 500

Powering Business Worldwide

Product specifications

Used with

Flat busbar
12 x 5/10 mm
15 x 5/10 mm
25 x 5/10 mm
20 x 5/10 mm
30 x 5/10 mm
60 mm system
System for flat busbar

Special features

Can be fitted to all busbar sizes using concertina system
With screw block inside

Type

60 mm system
System for flat busbar

Features

Self-extinguishing acc. UL 94
Halogen free

Frequency rating

50 Hz / 60 Hz

Creepage resistance

CTI 200

Current rating - max

630 A

Voltage rating

690 V

Ambient operating temperature - max

35 °C

Busbar distance

60 mm

Busbar temperature - max

70 °C

Rated insulation voltage (Ui)

3000 V

Short-circuit duration

Resources

Brochures

eaton-xeffect-sasy60i-customer-success-story-css-wagner-mueller-en-us.pdf

Catalogs

eaton-xeffect-sasy-60i-fk4300-1167gb-en-us.pdf

Product Range Catalog Switching and protecting motors

Certification reports

eaton-xeffect-sasy-60i-declaration-of-conformity.pdf

Drawings

eaton-control-panels-xeffect-sasy-busbar-support-dimensions-007.eps

eaton-control-panels-xeffect-sasy-busbar-support-3d-drawing-008.eps

20 ms

Number of poles

Four-pole

Color

Light gray (RAL 7035)

Distance between busbar centers

60 mm

Mounting position

Vertical, horizontal

Current rating (peak withstand)

64 kA (30 x 5 mm)
73 kA (30 x 10 mm)
56 kA (12 x 10 mm)
50 kA (20 x 5 mm)
50 kA (25 x 5 mm)
50 kA (12 x 5 mm)
56 kA (20 x 10 mm)

Functions

Busbar support
IEC busbar support

Frequency rating of contacts

50 Hz / 60 Hz

Temperature resistance

Up to 120 °C

Distance between busbar supports

250 mm

Rated operation current (Ie)

630 A

Suitable for

Four-pole

Flammability characteristics (UL)

Self-extinguishing (UL 94)

Material

Halogen free
Thermoplast, silicon free, chlorine free

Uninterrupted current (Iu) of bar

436 A (25 x 5 mm, Tu=35 °C and Ts=65 °C)
567 A (20 x 10 mm, Tu=35 °C and Ts=65 °C)
392 A (12 x 10 mm, Tu=35 °C and Ts=65 °C)
218 A (12 x 5 mm, Tu=35 °C and Ts=65 °C)

349 A (20 x 5 mm, Tu=35 °C and Ts=65 °C)

273 A (15 x 5 mm, Tu=35 °C and Ts=65 °C)

491 A (30 x 5 mm, Tu=35 °C and Ts=65 °C)

687 A (30 x 10 mm, Tu=35 °C and Ts=65 °C)

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia