Specifications

Eaton 197327



Catalog Number: 197327

Eaton DMM Switch-disconnector, DMM, 125 A, 4 pole, Emergency switching off function, With red rotary handle and yellow locking ring, in steel enclosure

General specifications

Product Name
Eaton DMM Switch-disconnector

Catalog Number
197327

EAN
4015081938742

Product Length/Depth
216 mm

Product Height
400 mm

Product Width
300 mm

Product Weight
7.75 kg

Certifications
IEC/EN 60204
IEC/EN 60947
VDE 0660
IEC/EN 60947-3
CE

Powering Business Worldwide

Features & Functions

Features

Version as emergency stop installation
Version as maintenance-/service switch
Version as main switch
Version as safety switch

Fitted with:

Red rotary handle and yellow locking ring

Functions

Interlockable
Emergency switching off function

Locking facility

Lockable in the 0 (Off) position

Number of poles

Four-pole

General

Accessories

Auxiliary contact fitted by user.

Degree of protection

NEMA 12

Degree of protection (front side)

IP65

Lifespan, mechanical

10,000 Operations

Mounting method

Surface mounting

Mounting position

As required

Overvoltage category

III

Pollution degree

3

Product Category

Main switch
Switch-disconnector

Product Category

Main switch
Switch-disconnector

Rated impulse withstand voltage (Uimp)

6000 V

Safety parameter (EN ISO 13849-1)

B10d values as per EN ISO 13849-1, table C.1

Suitable for

Ground mounting

Switching angle

90 °

Climatic environmental conditions

Ambient operating temperature - min

-25 °C

Terminal capacities

Terminal capacity

6 - 70 mm², flexible with ferrules to DIN 46228

Ambient operating temperature - max

55 °C

Ambient storage temperature - min

-30 °C

Ambient storage temperature - max

80 °C

Stripping length (main cable)

21 mm

Tightening torque

7 Nm, Screw terminals

Electrical rating

Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3)

1000 A

Rated breaking capacity at 500 V (cos phi to IEC 60947-3)

528 A

Rated breaking capacity at 660/690 V (cos phi to IEC 60947-3)

336 A

Rated insulation voltage (Ui)

690 V

Rated operational current (Ie) at AC-21, 400 V, 415 V

125 A

Rated operational current (Ie) at AC-21, 500 V

125 A

Rated operational current (Ie) at AC-21, 690 V

125 A

Rated operational current (Ie) at AC-22, 380 V, 400 V, 415 V

125 A

Rated operational current (Ie) at AC-22, 500 V

125 A

Rated operational current (Ie) at AC-22, 690 V

125 A

Rated operational current (Ie) at AC-23A, 400 V, 415 V

63 A

Rated operational current (Ie) at AC-23A, 500 V

63 A

Rated operational current (Ie) at AC-23A, 690 V

45 A

Rated operational power at AC-23A, 400 V, 50 Hz

30 kW

Rated operational power at AC-23A, 500 V, 50 Hz

45 kW

Rated operational power at AC-23A, 690 V, 50 Hz

40 kW

Rated operational power at AC-3, 380/400 V, 50 Hz

0 kW

Rated operational voltage (Ue) at AC - max

690 V

Rated uninterrupted current (Iu)

125 A

Uninterrupted current

Rated uninterrupted current Iu is specified for max. cross-section.

Short-circuit rating

Breaking current

13.7 kA

Let-through energy

Max. 134 kA²s

Rated conditional short-circuit current (Iq)

50 kA

Rated short-time withstand current (Icw)

2.5 kA

2,5 kA, Contacts, 1 second

Short-circuit protection rating

125, Fuse, Contacts

Contacts

Number of auxiliary contacts (change-over contacts)

0

Number of auxiliary contacts (normally closed contacts)

0

Number of auxiliary contacts (normally open contacts)

0

Actuator

Actuator color

Red

Actuator type

Long turning handle

Design verification

Heat dissipation per pole, current-dependent Pvid

4.9 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

Brochures

Steel enclosure brochure

Catalogs

P Switch-disconnectors and T Rotary cam switches catalogue CA042001EN

Declarations of conformity

DA-DC-00004933.pdf

DA-DC-00004903.pdf

Drawings

eaton-rotary-switches-dmm-switch-disconnector-dimensions.eps

eaton-rotary-switches-dmm-switch-disconnector-3d-drawing.eps

eaton-general-totally-insulated-t0-main-switch-symbol.eps

eaton-general-switch-t0-main-switch-symbol.eps

eaton-rotary-switches-t0-main-switch-symbol.eps

eCAD model

DA-CE-ETN.DMM-125_4_SE4_P-R

Installation instructions

IL008057ZU

Installation videos

Eaton Bussmann Switch Disconnect

Wiring diagrams

eaton-rotary-switches-switch-dmm-switch-disconnector-wiring-diagram.eps



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia