Date: 11/04/2023

PXA4ME 1 … 2,5 bar - 1/4 NPT-F - 1/2-14 NPT-M, with 1,5m cable

Mini pressure switch, flameproof enclosure Ex d

Item number: 68154121

Quantity: 1 pcs.

Order code: PXA4ME-BCAAB-1MAZZZZ-1ZZ ZCKW
F4-C5- - - - -

Overview:
PXA4ME 1 … 2,5 bar - 1/4 NPT-F - 1/2-14 NPT-M, with 1,5m cable
Mini pressure switch, flameproof enclosure Ex d PXA
switch enclosure: stainless steel 316L
measuring element: diaphragm with antagonist spring, Hastelloy C276, welded or with O-ring (1…2,5 to 6…25 bar)
contact version: 1xSPDT, silver contact, hermetically sealed
measuring range, working range, proof pressure: 1 … 2,5 bar, working range 0 … 10 bar, proof pressure 16 bar
Setting range depending on the switching direction: increasing 1,3…2,5 bar; decreasing 1...2,2 bar
Set point definition: Set Point not defined
Mounting: direct mounting
Connection: Stainless steel AISI 316LBrand: WIKA Instruments Italia
Ingress Protection: IP66
Specifications according to data sheet: PV 34.38
Repeatability of set point: ≤ 1% of end of setting range

Approvals / Certificates
IECEx-ATEX Ex d

Details:
Mini pressure switch, flameproof enclosure Ex d
Model PXA
Specifications according to data sheet: PV 34.38
Repeatability of set point: ≤ 1% of end of setting range
measuring element: diaphragm with antagonist spring, Hastelloy C276, welded or with O-ring (1…2,5 to 6…25 bar)
contact version: 1xSPDT, silver contact, hermetically sealed
measuring range, working range, proof pressure: 1 … 2,5 bar, working range 0 … 10 bar, proof pressure 16 bar
Setting range depending on the switching direction: increasing 1,3…2,5 bar; decreasing 1...2,2 bar
Set Point not defined
Process connection: 1/4 NPT-F
Electrical connection: 1/2-14 NPT-M, with 1,5m cable
Mounting: direct mounting
Brand: WIKA Instruments Italia
Ingress Protection: IP66

© 2023 - WIKA Instruments s.a.r.l.

Connection: Stainless steel AISI 316L
PXA4ME
Approvals / Certificates
IECEx-ATEX Ex d

© 2023 - WIKA Instruments s.a.r.l.