TIMKEN

The Timken Company
4500 Mt Pleasant St. NW
N. Canton, OH 44720
Phone: (234) 262-3000
E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Timken Part Number 387 - 382, Tapered Roller Bearings - TS (Tapered Single) Imperial

This is the most basic and most widely used type of tapered roller bearing. It consists of two main separable parts: the cone (inner ring) assembly and the cup (outer ring). It is typically mounted in opposing pairs on a shaft.





Specifications | Dimensions | Abutment and Fillet Dimensions | Basic Load Ratings | Factors

Specifications

Series	385
Cone Part Number	387
Cup Part Number	382
Design Units	Imperial
Bearing Weight	1.40 lb 0.600 Kg
Cage Type	Stamped Steel

Dimensions

d - Bore	2.2500 in 57.150 mm
D - Cup Outer Diameter	3.8750 in 98.425 mm

B - Cone Width	0.8640 in 21.946 mm
C - Cup Width	0.7018 in 17.826 mm
T - Bearing Width	0.8268 in 21.001 mm

Abutment and Fillet Dimensions

R - Cone Backface "To Clear" Radius[1]	0.090 in 2.290 mm
r - Cup Backface "To Clear" Radius[2]	0.030 in 0.76 mm
da - Cone Frontface Backing Diameter	2.48 in 62.99 mm
db - Cone Backface Backing Diameter	2.64 in 67.06 mm
Da - Cup Frontface Backing Diameter	3.66 in 92.96 mm
Db - Cup Backface Backing Diameter	3.54 in 89.92 mm
Ab - Cage-Cone Frontface Clearance	0.11 in 2.8 mm
Aa - Cage-Cone Backface Clearance	0.03 in 0.8 mm
a - Effective Center Location[3]	-0.12 in -3.00 mm

Basic Load Ratings

C90 - Dynamic Radial Rating (90 million revolutions)[4]	6280 lbf 28000 N
C1 - Dynamic Radial Rating (1 million revolutions)[5]	24200 lbf 108000 N
C0 - Static Radial Rating	24100 lbf 107000 N
C_{a90} - Dynamic Thrust Rating (90 million revolutions)[6]	3810 lbf 16900 N

Factors

K - Factor[7]	1.65
e - ISO Factor[8]	0.35
Y - ISO Factor[9]	1.69
G1 - Heat Generation Factor (Roller-Raceway)	42
G2 - Heat Generation Factor (Rib-Roller End)	15.7
Cg - Geometry Factor	0.0859

[1] These maximum fillet radii will be cleared by the bearing corners.
[2] These maximum fillet radii will be cleared by the bearing corners.
[3] Negative value indicates effective center inside cone backface.
[4] Based on 90 x 10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values.
[5] Based on 1 x 10^6 revolutions L_{10} life, for the ISO life calculation method.
[6] Based on 90 x 10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.
[7] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.
[8] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.
[9] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.



IMPERIAL UNITS

ISO Factor - e	0.35	
ISO Factor - Y	1.69	
Bearing Weight	1.4	lb
Number of Rollers Per Row	19	
Effective Center Location	-0.12	inch

TIMKEN®

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

387 - 382
TS BEARING ASSEMBLY

K Factor	1.65	
Dynamic Radial Rating - C90	6280	lbf
Dynamic Thrust Rating - Ca90	3810	lbf
Static Radial Rating - C0	24100	lbf
Dynamic Radial Rating - C1	24200	lbf

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY