*Date: 24/01/2024*

# 232.50.160 250 bar G1/2B lower mount

## Bourdon Tube Pressure Gauges, Stainless Steel

| | |
|---|---|
| Item number: | 9050175 |
| Quantity: | 1 pcs. |
| Order code: | 232.50-F-BG525Z-GD-UZHZCZZ-ZZZZZZZ 213D31ZI3W0 Z2Z-IZZZZZZ12ZZZ<br>LABEL-PG1DE-ZZZZZ |
| Overview: | 232.50.160 250 bar G1/2B lower mount<br>Measuring System 316L<br>Ingress protection: IP 65<br>class 1.0<br>Window: laminated safety glass<br>Permissible ambient temperature: -40 … +60 °C<br>Permissible medium temperature: + 200 °C<br>Pressure Gauge Standard: International (standard Europe)<br>*WIKA*<br>with Serial number<br>Label: WIKA standard without / with Tag-number |
| Details: | Bourdon Tube Pressure Gauges, Stainless Steel<br>Series<br>Model: 232.50<br>Specifications according to data sheet: PM 02.02<br>Measuring system: stainless steel<br>Case filling: without<br>Nominal size: 160 mm<br>Scale range: 0...250 bar<br>Process connection: G 1/2 B<br>Connector location: lower mount<br>Window: laminated safety glass<br>Pointer: standard pointer<br>Accuracy class: class 1.0<br>Overpressure safe: standard<br>Case material: Stainless steel 1.4301<br>Case surface: bare<br>Material pressure element: Measuring System 316L<br>Case filling fluid: prepared for filling<br>Ingress protection: IP 65<br>Permissible medium temperature: + 200 °C<br>Permissible ambient temperature: -40 … +60 °C<br>Movement: stainless steel<br>Packaging: single packing<br>Pressure Gauge Standard: International (standard Europe)<br>Manufacturer logo: *WIKA* |

*© 2024 - WIKA Instruments s.a.r.l.*

*Date: 24/01/2024*

with Serial number

*© 2024 - WIKA Instruments s.a.r.l.*