PRODUCT-DETAILS

CA5-40NRT

CA5-40NRT Auxiliary Contact Block



General Information

Extended Product Type	CA5-40NRT
Product ID	1SBN010042R1240
EAN	3471522364630
Catalog Description	CA5-40NRT Auxiliary Contact Block
Long Description	CA5-40NRT is a 4-pole front mounted auxiliary contact block equipped with screw terminals for connection with ring tongue ferrules. CA5-..N version offers terminal assortment matching the marking of 4-pole TNL..ERT contactors. CA5-40NRT is available with 4 N.O. and 0 N.C. instantaneous contacts for standard industrial environments.

Ordering

Minimum Order Quantity	2 piece
Customs Tariff Number	85389099

Popular Downloads

Data Sheet, Technical	1SBC100122C0202_Ch04

© 2024 ABB. All rights reserved.

Information	
Instructions and Manuals	1SBC101011M5501
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	43 mm
Product Net Depth / Length	39 mm
Product Net Height	47 mm
Product Net Weight	0.06 kg

Technical

Number of Auxiliary Contacts NO	4
Number of Auxiliary Contacts NC	0
Rated Operational Voltage	Auxiliary Circuit 690 V
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz
Rated Operational Current AC-15 (I_e)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (380 / 400 V) 3 A
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 0.1 s 140 A for 1 s 100 A
Rated Operational Current DC-13 (I_e)	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.30 A / 66 W (250 V) 0.3 / 75 W
Rated Insulation Voltage (U_i)	acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP10
Terminal Type	Ring-Tongue Terminals
Suitable For	N22E N31E N40E NL22E NL31E NL40E TNL22E TNL31E TNL40E

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

© 2024 ABB. All rights reserved.

WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CB Certificate	CB_SE_62119A1
CCC Certificate	CCC_2015010304800518
CQC Certificate	CQC2015010304800518 CQC2004010305133985
Declaration of Conformity - CCC	2020980304001627 2020980305001185
Declaration of Conformity - CE	1SBD250809U1000
Declaration of Conformity - UKCA	1SBD250826U1000
EAC Certificate	EAC_RU C-FR ME77 B03391
GOST Certificate	GOST_POCCFRME77B07174
RINA Certificate	RINA_ELE172319XG001

Container Information

Package Level 1 Units	2 piece
Package Level 1 Width	65 mm
Package Level 1 Depth / Length	129.5 mm
Package Level 1 Height	43 mm
Package Level 1 Gross Weight	0.12 kg
Package Level 1 EAN	3471522364630
Package Level 2 Units	32 piece
Package Level 2 Gross Weight	1.92 kg
Package Level 3 Units	2880 piece

Classifications

Object Classification Code	K
ETIM 7	EC000041 - Auxiliary contact block
ETIM 8	EC000041 - Auxiliary contact block
ETIM 9	EC000041 - Auxiliary contact block
eClass	V11.0 : 27371302
UNSPSC	39121522
IDEA Granular Category Code (IGCC)	4743 >> Auxiliary contact block

© 2024 ABB. All rights reserved.

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors



© 2024 ABB. All rights reserved.