PRODUCT-DETAILS

AF96-30-00-13

AF96-30-00-13 100-250V50/60HZ-DC Contactor



General Information

Extended Product Type	AF96-30-00-13
Product ID	1SBL407001R1300
EAN	3471523133235
Catalog Description	AF96-30-00-13 100-250V50/60HZ-DC Contactor
Long Description	The AF96-30-00-13 is a 3 pole - 1000 V IEC or 600 UL contactor with screw terminals, controlling motors up to 45 kW / 400 V AC (AC-3) or 60 hp / 480 V UL and switching power circuits up to 130 A (AC-1) or 115 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (100-250 V 50/60 Hz and DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Instructions and Manuals	1SBC101036M6801
CAD Dimensional	2CDC001079B0201

© 2024 ABB. All rights reserved.

Subject to change without notice

Drawing

Dimensions

Product Net Width	70 mm
Product Net Depth / Length	116 mm
Product Net Height	125.5 mm
Product Net Weight	1.17 kg

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	0
Standards	IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60947-1, UL 60947-4-1, CSA C22.2 No. 60947-1:22, CSA C22.2 No. 60947-4-1:22
Rated Operational Voltage	Main Circuit 1000 V
Rated Frequency (f)	Control Circuit 50 / 60 Hz Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-4-1, Open Contactors Θ = 40 °C 130 A
Rated Operational Current AC-1 (I_e)	(690 V) 40 °C 130 A (690 V) 60 °C 105 A (690 V) 70 °C 90 A
Rated Operational Current AC-3 (I_e)	(415 V) 60 °C 96 A (440 V) 60 °C 96 A (500 V) 60 °C 80 A (690 V) 60 °C 57 A (1000 V) 60 °C 30 A (380 / 400 V) 60 °C 105 A (220 / 230 / 240 V) 60 °C 105 A
Rated Operational Current AC-3e (I_e)	(415 V) 60 °C 96 A (440 V) 60 °C 96 A (500 V) 60 °C 80 A (690 V) 60 °C 57 A (380 / 400 V) 60 °C 105 A (220 / 230 / 240 V) 60 °C 105 A
Rated Operational Power AC-3 (P_e)	(415 V) 55 kW (440 V) 55 kW (500 V) 55 kW (690 V) 55 kW (1000 V) 40 kW (380 / 400 V) 45 kW (380 / 400 V) 55 kW (220 / 230 / 240 V) 25 kW (220 / 230 / 240 V) 30 kW
Rated Operational Power AC-3e (P_e)	(415 V) 55 kW (440 V) 55 kW (500 V) 55 kW (690 V) 55 kW (380 / 400 V) 45 kW (380 / 400 V) 55 kW (220 / 230 / 240 V) 25 kW (220 / 230 / 240 V) 30 kW
Rated Short-time Withstand Current Low Voltage (I_{cw})	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 840 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 140 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 300 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1200 A

© 2024 ABB. All rights reserved.

	at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 450 A
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for Ie > 100 A) at 440 V 1150 A cos phi=0.45 (cos phi=0.35 for Ie > 100 A) at 690 V 750 A
Maximum Electrical Switching Frequency	(AC-1) 600 cycles per hour (AC-2 / AC-4) 150 cycles per hour (AC-3) 1200 cycles per hour
Rated Operational Current DC-1 (I_e)	(110 V) 2 Poles in Series, 40 °C 130 A (110 V) 2 Poles in Series, 60 °C 105 A (110 V) 2 Poles in Series, 70 °C 90 A (110 V) 3 Poles in Series, 40 °C 130 A (110 V) 3 Poles in Series, 60 °C 105 A (110 V) 3 Poles in Series, 70 °C 90 A (220 V) 3 Poles in Series, 40 °C 125 A (220 V) 3 Poles in Series, 60 °C 105 A (220 V) 3 Poles in Series, 70 °C 90 A (72 V) 1-Pole, 40 °C 130 A (72 V) 1-Pole, 60 °C 105 A (72 V) 1-Pole, 70 °C 90 A (72 V) 2 Poles in Series, 40 °C 130 A (72 V) 2 Poles in Series, 60 °C 105 A (72 V) 2 Poles in Series, 70 °C 90 A (72 V) 3 Poles in Series, 40 °C 130 A (72 V) 3 Poles in Series, 60 °C 105 A (72 V) 3 Poles in Series, 70 °C 90 A
Rated Operational Current DC-3 (I_e)	(110 V) 2 Poles in Series, 40 °C 130 A (110 V) 2 Poles in Series, 60 °C 105 A (110 V) 2 Poles in Series, 70 °C 90 A (110 V) 3 Poles in Series, 40 °C 130 A (110 V) 3 Poles in Series, 60 °C 105 A (110 V) 3 Poles in Series, 70 °C 90 A (220 V) 3 Poles in Series, 40 °C 130 A (220 V) 3 Poles in Series, 60 °C 105 A (220 V) 3 Poles in Series, 70 °C 90 A (72 V) 1-Pole, 40 °C 130 A (72 V) 1-Pole, 60 °C 105 A (72 V) 1-Pole, 70 °C 90 A (72 V) 2 Poles in Series, 40 °C 130 A (72 V) 2 Poles in Series, 60 °C 105 A (72 V) 2 Poles in Series, 70 °C 90 A (72 V) 3 Poles in Series, 40 °C 130 A (72 V) 3 Poles in Series, 60 °C 105 A (72 V) 3 Poles in Series, 70 °C 90 A
Rated Operational Current DC-5 (I_e)	(110 V) 2 Poles in Series, 40 °C 130 A (110 V) 2 Poles in Series, 60 °C 105 A (110 V) 2 Poles in Series, 70 °C 90 A (110 V) 3 Poles in Series, 40 °C 130 A (110 V) 3 Poles in Series, 60 °C 105 A (110 V) 3 Poles in Series, 70 °C 90 A (220 V) 3 Poles in Series, 40 °C 130 A (220 V) 3 Poles in Series, 60 °C 105 A (220 V) 3 Poles in Series, 70 °C 90 A (72 V) 1-Pole, 40 °C 130 A (72 V) 1-Pole, 60 °C 105 A (72 V) 1-Pole, 70 °C 90 A (72 V) 2 Poles in Series, 40 °C 130 A (72 V) 2 Poles in Series, 60 °C 105 A (72 V) 2 Poles in Series, 70 °C 90 A (72 V) 3 Poles in Series, 40 °C 130 A (72 V) 3 Poles in Series, 60 °C 105 A (72 V) 3 Poles in Series, 70 °C 90 A
Rated Insulation Voltage (U_i)	acc. to IEC 60947-4-1 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Maximum Mechanical Switching Frequency	3600 cycles per hour
Rated Control Circuit Voltage (U_c)	50 Hz 100 ... 250 V 60 Hz 100 ... 250 V DC Operation 100 ... 250 V
Coil Consumption	Average Holding Value 50 / 60 Hz 4 V·A Average Holding Value 50 Hz 4 V·A Average Holding Value 60 Hz 4 V·A Average Holding Value DC 2 W Average Holding Value, from Warm State 2 W

© 2024 ABB. All rights reserved.

Operate Time	Between Coil De-energization and NC Contact Closing 19 ... 105 ms Between Coil De-energization and NO Contact Opening 17 ... 100 ms Between Coil Energization and NC Contact Opening 38 ... 95 ms Between Coil Energization and NO Contact Closing 42 ... 100 ms
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Mounting by Screws (not supplied)	2 x M4 or 2 x M6 screws placed diagonally
Connecting Capacity Main Circuit	Flexible with Ferrule 1/2x 6 ... 50 mm² Flexible with Insulated Ferrule 1/2x 6 ... 50 mm² Rigid Stranded 1x 6 ... 70 mm² Rigid Stranded 2x 6 ... 50 mm²
Connecting Capacity Control Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm² Rigid Solid 1/2x 1 ... 2.5 mm² Rigid Stranded 1/2x 1 ... 2.5 mm²
Wire Stripping Length	Control Circuit 10 mm Main Circuit 17 mm
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Terminal Type	Screw Terminals

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V
General Use Rating UL/CSA	(600 V AC) 115 A
Horsepower Rating UL/CSA	(120 V AC) Single Phase 7-1/2 hp (200 ... 208 V AC) Three Phase 30 hp (220 ... 240 V AC) Three Phase 40 hp (240 V AC) Single Phase 20 hp (440 ... 480 V AC) Three Phase 75 hp (550 ... 600 V AC) Three Phase 75 hp
Connecting Capacity Main Circuit UL/CSA	Rigid Stranded 1/2x 6-1 AWG
Connecting Capacity Control Circuit UL/CSA	Rigid Solid 1/2x 18-14 AWG Rigid Stranded 1/2x 18-14 AWG
Tightening Torque UL/CSA	Control Circuit 11 in·lb Main Circuit 53 in·lb

Environmental

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay -40 ... 70 °C Close to Contactor without Thermal O/L Relay -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C
Climatic Withstand	Category B according to IEC 60947-1 Annex Q
Maximum Operating Altitude Permissible	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27	Closed, Shock Direction: A 25 g Closed, Shock Direction: B1 25 g Closed, Shock Direction: B2 15 g Closed, Shock Direction: C1 25 g Closed, Shock Direction: C2 25 g Open, Shock Direction: B1 5 g
Resistance to Vibrations	3g Closed Position & 3g Open Position 5 ... 300 Hz

Material Compliance

Conflict Minerals Reporting Template	9AKK108467A5658

© 2024 ABB. All rights reserved.

(CMRT)	
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

ABS Certificate	ABS_20-2060694-PDA
BV Certificate	BV_2634H36994B1
CB Certificate	CB_SE-96557M3
CCC Certificate	CCC_2013010304646569
CQC Certificate	CQC2013010304646569
Declaration of Conformity - CCC	2020980304001255
Declaration of Conformity - CE	1SBD250000U1000
Declaration of Conformity - UKCA	1SBD250031U1000
DNV Certificate	DNV_TAE00001AF-4
EAC Certificate	EAC_RU_FRME77B03447
KC Certificate	KC_HW02016-15011C
LR Certificate	LRS_LR23403517TA-02
RINA Certificate	RINA_ELE084013XG
RMRS Certificate	RMRS_1802705280
UL Certificate	UL-US-L312527-1141-10303102-9 UL-CA-L312527-4141-10303102-9
UL Listing Card	UL_E312527

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	150 mm
Package Level 1 Depth / Length	150 mm
Package Level 1 Height	103 mm
Package Level 1 Gross Weight	1.29 kg
Package Level 1 EAN	3471523133235
Package Level 2 Units	box 8 piece
Package Level 2 Width	250 mm
Package Level 2 Depth / Length	300 mm
Package Level 2 Height	300 mm
Package Level 2 Gross Weight	10.32 kg
Package Level 3 Units	192 piece

Classifications

Object Classification Code	Q

© 2024 ABB. All rights reserved.

ETIM 4	EC000066 - Magnet contactor, AC-switching
ETIM 5	EC000066 - Magnet contactor, AC-switching
ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4758 >> Iec Contactors
E-Number (Finland)	3707137
E-Number (Sweden)	3210057

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → AF Contactors → AF96



© 2024 ABB. All rights reserved.