Rittal – The System.

Faster – better – everywhere.

Monitor/keyboard unit with 17" TFT display and VGA/DVI connection – DK 9055.410

Date : Apr 26, 2021

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Monitor/keyboard unit with 17" TFT display and VGA/DVI connection – DK 9055.410

created: 26.04.2021 build on www.rittal.com/uk-en



Product description

Description:	The unit is housed in a pull-out drawer. The monitor can be flipped up and the drawer latches into the end position. This means that the unit only requires 1 U in the 482.6 mm (19") rack.
Benefits:	Analog and digital video input Cables are safely routed in the energy chain Lockable at the front Simple, one-man installation.
Colour:	RAL 9005
Supply includes:	Monitor/keyboard unit, 1 U VGA cable DVI cable USB cable Earthing-pin mains cable with 17" TFT display and VGA/DVI connection 2 PS/2 cables Keyboard with integral touchpad
Note on Model No.:	Extended delivery times.

Product description

Dimensions:	Width: 482.6 mm Width: 19" Depth: 680 mm
Rated operating voltage:	100 V - 240 V, 1~, 50 Hz/60 Hz

Units:	1 U
Installation dimensions:	Installation depth (min.): 680 mm Installation depth (max.): 850 mm
Operating temperature:	Operation (environment): +5 °C...+45 °C
Power consumption:	Max. power consumption in operation: 32 W Max. power consumption with closed monitor unit: 1 W
Equipment (electrical):	Connector (type): IEC 320 connector C14
Keyboard layout:	German
Display features:	Diagonal: 432 mm (17") Format: 4 : 3 Resolution of display: 1280 x 1024 pixels Number of colours: 16700000 Brightness (typ.): 350 cd/m² Contrast ratio: Contrast ratio approx. 1000:1
Interfaces/connections:	General: VGA (D-Sub HD 15-pole) General: DVI General: 1 x USB General: PS/2
Packs of:	1 pc(s).
Weight/pack:	18.8 kg
Copper weight (kg per piece):	0
EAN:	4028177638396
Customs tariff number:	85286200
ETIM 7.0:	EC001428
ETIM 6.0:	EC001428
eCl@ss 8.0/8.1:	19200201
eCl@ss 6.0/6.1:	27189253
Product description:	DK Monitor/keyboard unit, WHD: 482.6 mm (19")x1 Ux680 mm, 100-240 V, 1~, 50/60 Hz, german, RAL 9005

Approvals

Certificates:	EAC
Declarations:	Declaration of conformity