


LED-Maschinenleuchte



Product-Nr.	111010-35
EAN:	4260556624259
Model:	LEANLED II opalweiß kaskadierbar







Order number:	111010-35
Model:	LEANLED II opalweiß kaskadierbar
Type:	LED surface-mounted luminaire
Illuminant:	SMD LED
Power consumption:	~19 W
Lamp luminous flux:	3004 lm
Lamp luminous efficiency:	155 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC ± 10%
Connection (connector):	M12 A-type encoded
Degree of protection:	IP54
Class of protection:	III
Glare control:	opal white
Beam angle (optics):	120°
Operating temperature:	-10... +60 °C (14… 140 °F)
Colour rendering (Ra):	> 85
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium
Cover material:	Polycarbonate, soft
Height [B] x Width [C]:	31 mm x 26 mm (1,22“ x 1,02“)
Length [A]:	760 mm (29,92“)
Weight (net):	500 g (~18 oz)
Gross weight:	800 g (~28 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003526)
Dimmable:	via optional accessory
Mounting accessories:	2 pairs mounting holders (holder for swivel or planar moun-ting) in delivery scope
Made in:	Germany
Feature:	cascadable, several luminiares can be interlinked electrically.

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com