Specifications

Eaton 302458



Catalog Number: 302458

Eaton xComfort KLV LV systems Final Distribution Boards. Compact distribution board-flush mounting, Hybrid, 5-rows, 36MU, flat sheet steel door WIFI, 60UPS-W-HY36-F

General specifications

Product Name
Eaton xComfort KLV hybrid distribution board

Catalog Number
302458

EAN
9010238161276

Product Length/Depth
100 mm

Product Height
840 mm

Product Width
360 mm

Product Weight
6.39 kg

Compliances
RoHS conform

Certifications
IEC/EN 60670-24 (PD)
IEC/EN 62208

Powering Business Worldwide

Product specifications

Used with

Basic device

Installation distribution boards

KLV hybrid WIFI

Special features

IP30 Protection Class II Plastic housing with Wi-Fi door, white (RAL 9016) Note: To obtain protection class II, all devices installed on the mounting plate must be of the fully insulated type.

Type

Basic device Installation distribution boards KLV hybrid WIFI

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility.

10.13 Mechanical function

Meets the product standard's requirements.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

650 °C; meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Not relevant to indoor installations.

10.2.5 Lifting

Does not apply to enclosures without lifting aids.

10.2.6 Mechanical impact

IK05

10.2.7 Inscriptions

Resources

Brochures

eaton-xcomfort-compact-distribution-boxes-brochure-br014015en-en-us.pdf

Catalogs

eaton-xcomfort-compact-distribution-catalog-ca015004en-en-us.pdf

Declarations of conformity

DA-DC-03_xComfort_KLV

DA-DC-03_KLV-36-F-2PXF-16PLI

Drawings

eaton-lighting-xcomfort-klv-lv-systems-dimensions-016.eps

eaton-lighting-xcomfort-klv-lv-systems-dimensions-013.eps

Installation instructions

IL014007ZU

eaton-compact-distribution-board-klv-il014064zu.pdf

Installation videos

New xComfort KLV 5-row series

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

IP30

10.4 Clearances and creepage distances

Is the panel builder's responsibility.

10.5 Protection against electric shock

Protection class 2, therefore not applicable.

10.6 Incorporation of switching devices and components

Is the panel builder's responsibility.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Ui = 400 V AC

10.9.3 Impulse withstand voltage

4 kV

10.9.4 Testing of enclosures made of insulating material

Meets the product standard's requirements.

Fitted with:

Imprintable sheet
WIFI Door/Frame
Spirit level for leveling
3D adjustment element for mounting designed to adjust the mounting depth by up to 18 mm
Cable retainer
Microperforated mounting plate
Device support rails
Wall trough
Device holder
Neutral and protective conductor terminals with SK screw terminal technology
Mounting plate
Nail lugs
1x single-way socket outlet
Front cover
Installation instructions

Enclosure material

Plastic

Built-in height

0 mm

Built-in width

0 mm

Cable entry postion

Cable entries on top and bottom, side, back plate

Terminal type

Screw terminals

Built-in depth

80 mm

Heat diss. ambient 35°C delta T:20°C flush mount individ. encl. top(IEC 60890)

28 W

Heat diss. ambient 35°C delta T:35°C flush mount individ. encl. top(IEC 60890)

58 W

Closure type

Other

Cover/door color

White

Cover/door model

With notch

Cover/door type

Door

Single

RAL-number

9016

Width in number of modular spacings

12

Ambient operating temperature details

-5 °C - 40 °C

Application

Indoor

Voltage rating at AC

400 V AC

Color

White

Traffic white (RAL 9016)

Number of rows

5

Frequency rating of contacts

50 Hz

Module rack type

Rail frame / Media mounting plate

Degree of protection

IK05

IP30

Number of module space units per row

12

Protection class

II (totally insulated)

Protective shrouding material

Plastic

Functions

Extension possible

Basic device

Material

Polystyren (plastic)

Sheet steel, powder-coated

Mounting method

DIN-rail

Flush mounted (plaster)

Flush mounting

Internal depth

80 mm

PE and N terminal number and cross section

N: 25 x (0.75 mm² - 16 mm²)

N - Fi: 2 x (0.75 mm² - 16 mm²) + 2 x (0.75 mm² - 25 mm²)

PE: 25 x (0.75 mm² - 16 mm²)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia