PRODUCT-DETAILS

# AF40-30-22-13

## AF40-30-22-13 100-250V50/60HZ-DC Contactor



### General Information

| | |
|---|---|
| Extended Product Type | AF40-30-22-13 |
| Product ID | 1SBL347001R1322 |
| EAN | 3471523132238 |
| Catalog Description | AF40-30-22-13 100-250V50/60HZ-DC Contactor |
| Long Description | The AF40-30-22-13 is a 3 pole - 690 V IEC or 600 UL contactor with pre-mounted auxiliary contacts and screw terminals, controlling motors up to 18.5 kW / 400 V AC (AC-3) or 30 hp / 480 V UL and switching power circuits up to 70 A (AC-1) or 60 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (100-250 V 50/60 Hz and DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories. |

### Ordering

| | |
|---|---|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85364900 |

### Popular Downloads

| | |
|---|---|
| Instructions and Manuals | 1SBC101036M6801 |

## Dimensions

| | |
|---|---|
| Product Net Width | 55 mm |
| Product Net Depth / Length | 144 mm |
| Product Net Height | 125.5 mm |
| Product Net Weight | 1 kg |

## Technical

| | |
|---|---|
| Number of Main Contacts NO | 3 |
| Number of Main Contacts NC | 0 |
| Number of Auxiliary Contacts NO | 2 |
| Number of Auxiliary Contacts NC | 2 |
| Rated Operational Voltage | Auxiliary Circuit 690 V<br>Main Circuit 690 V |
| Rated Frequency (f) | Auxiliary Circuit 50 / 60 Hz<br>Main Circuit 50 / 60 Hz |
| Conventional Free-air Thermal Current ($I_{th}$) | acc. to IEC 60947-4-1, Open Contactors q = 40 °C 105 A<br>acc. to IEC 60947-5-1, q = 40 °C 16 A |
| Rated Operational Current AC-1 ($I_e$) | (690 V) 40 °C 70<br>(690 V) 60 °C 60 A<br>(690 V) 70 °C 50 |
| Rated Operational Current AC-3 ($I_e$) | (415 V) 60 °C 40 A<br>(440 V) 60 °C 40 A<br>(500 V) 60 °C 35 A<br>(690 V) 60 °C 25 A<br>(380 / 400 V) 60 °C 40 A<br>(220 / 230 / 240 V) 60 °C 40 A |
| Rated Operational Power AC-3 ($P_e$) | (400 V) 18.5 kW<br>(415 V) 22 kW<br>(440 V) 22 kW<br>(500 V) 22 kW<br>(690 V) 22 kW<br>(380 / 400 V) 18.5 kW<br>(220 / 230 / 240 V) 11 kW |
| Rated Operational Current AC-15 ($I_e$) | (500 V) 2 A<br>(690 V) 2 A<br>(24 / 127 V) 6 A<br>(220 / 240 V) 4 A<br>(400 / 440 V) 3 A |
| Rated Short-time Withstand Current ($I_{cw}$) | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 600 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 110 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 250 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1000 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 350 A<br>for 0.1 s 140 A<br>for 1 s 100 A |
| Maximum Breaking Capacity | cos phi=0.45 (cos phi=0.35 for Ie > 100 A) at 440 V 950 A<br>cos phi=0.45 (cos phi=0.35 for Ie > 100 A) at 690 V 600 A |
| Maximum Electrical Switching Frequency | (AC-1) 600 cycles per hour<br>(AC-15) 1200 cycles per hour<br>(AC-2 / AC-4) 150 cycles per hour<br>(AC-3) 1200 cycles per hour<br>(DC-13) 900 cycles per hour |
| Rated Operational Current DC-13 ($I_e$) | (24 V) 6 A / 144 W<br>(48 V) 2.8 A / 134 W<br>(72 V) 1 A / 72 W<br>(110 V) 0.55 A / 60 W<br>(125 V) 0.55 A / 69 W<br>(220 V) 0.27 A / 60 W<br>(250 V) 0.27 A / 68 W<br>(400 V) 0.15 A / 60 W<br>(500 V) 0.13 A / 65 W |

| | |
|---|---|
| | (600 V) 0.1 A / 60 W |
| Rated Insulation Voltage ($U_i$) | acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 690 V<br>acc. to UL/CSA 600 V |
| Rated Impulse Withstand Voltage ($U_{imp}$) | 6 kV |
| Maximum Mechanical Switching Frequency | 3600 cycles per hour |
| Rated Control Circuit Voltage ($U_C$) | 50 Hz 100 ... 250 V<br>50 Hz / 60 Hz 100 ... 250 V<br>60 Hz 100 ... 250 V<br>DC Operation 100 ... 250 V |
| Operate Time | Between Coil De-energization and NC Contact Closing 19 ... 105 ms<br>Between Coil De-energization and NO Contact Opening 17 ... 100 ms<br>Between Coil Energization and NC Contact Opening 38 ... 95 ms<br>Between Coil Energization and NO Contact Closing 42 ... 100 ms |
| Connecting Capacity Main Circuit | Flexible with Ferrule 1/2x 4 ... 35 mm²<br>Flexible with Insulated Ferrule 1/2x 4 ... 35 mm²<br>Rigid 1/2x 6 ... 3 5 mm² |
| Connecting Capacity Auxiliary Circuit | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm²<br>Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm²<br>Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm²<br>Rigid 1/2x 1 ... 2.5 mm² |
| Connecting Capacity Control Circuit | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm²<br>Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm²<br>Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm²<br>Rigid 1/2x 1 ... 2.5 mm² |
| Wire Stripping Length | Main Circuit 16 mm |
| Degree of Protection | acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP40<br>acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20<br>acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10 |
| Terminal Type | Screw Terminals |

## Technical UL/CSA

| | |
|---|---|
| General Use Rating UL/CSA | (600 V AC) 60 A |
| Horsepower Rating UL/CSA | (120 V AC) Single Phase 3 hp<br>(200 ... 208 V AC) Three Phase 10 hp<br>(220 ... 240 V AC) Three Phase 15 hp<br>(240 V AC) Single Phase 7-1/2 hp<br>(440 ... 480 V AC) Three Phase 30 hp<br>(550 ... 600 V AC) Three Phase 40 hp |
| Tightening Torque UL/CSA | Auxiliary Circuit 11 lA<br>Control Circuit 11 lA<br>Main Circuit 35 lA |

## Environmental

| | |
|---|---|
| Ambient Air Temperature | Close to Contactor Fitted with Thermal O/L Relay -25 ... +60 °C<br>Close to Contactor without Thermal O/L Relay -40 ... +70 °C<br>Close to Contactor for Storage -60 ... +80 °C |
| Climatic Withstand | Category B according to IEC 60947-1 Annex Q |
| Maximum Operating Altitude Permissible | 3000 m |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 5 ... 300 Hz 3 g closed position / 3 g open position |
| Resistance to Shock acc. to IEC 60068-2-27 | Closed, Shock Direction: A 25 K40<br>Closed, Shock Direction: B1 25 K40<br>Closed, Shock Direction: B2 15 K40<br>Closed, Shock Direction: C1 25 K40<br>Closed, Shock Direction: C2 25 K40<br>Open, Shock Direction: B1 5 K40 |
| RoHS Status | Following EU Directive 2011/65/EU |

## Certificates and Declarations (Document Number)

| | |
|---|---|
| ABS Certificate | ABS_15-GE1349500-PDA_90682247 |
| BV Certificate | BV_2634H36994A |
| CB Certificate | CB_SE-96554 |
| CCC Certificate | CCC_2012010304589737<br>CCC_2015010304824714 |
| CQC Certificate | CQC2015010304824714<br>CQC2012010304589737 |
| Declaration of Conformity - CCC | 2020980304001256<br>2020980304001074 |
| Declaration of Conformity - CE | 1SBD250000U1000 |
| DNV Certificate | DNV-GL_TAE00001AF-3 |
| DNV GL Certificate | DNV-GL_TAE00001AF-3 |
| EAC Certificate | EAC_RU_FRME77B03447 |
| Environmental Information | 1SBD250168E1000 |
| GL Certificate | DNV-GL_TAE00001AF-3 |
| Instructions and Manuals | 1SBC101036M6801 |
| KC Certificate | KC_HW02016-15006C |
| LR Certificate | LRS_1300087E1 |
| RINA Certificate | RINA_ELE084013XG |
| RMRS Certificate | RMRS_1802705280 |
| RoHS Information | 1SBD250000U1000 |
| UL Certificate | UL_20130926-E312527_14_1 |
| UL Listing Card | UL_E312527 |

## Container Information

| | |
|---|---|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 180 mm |
| Package Level 1 Depth / Length | 150 mm |
| Package Level 1 Height | 102 mm |
| Package Level 1 Gross Weight | 1.14 kg |
| Package Level 1 EAN | 3471523132238 |
| Package Level 2 Units | box 6 piece |
| Package Level 2 Width | 250 mm |
| Package Level 2 Depth / Length | 300 mm |
| Package Level 2 Height | 300 mm |
| Package Level 2 Gross Weight | 6.84 kg |
| Package Level 3 Units | 144 piece |

## Classifications

| | |
|---|---|
| Object Classification Code | Q |
| ETIM 4 | EC000066 - Magnet contactor, AC-switching |
| ETIM 5 | EC000066 - Magnet contactor, AC-switching |
| ETIM 6 | EC000066 - Power contactor, AC switching |
| ETIM 7 | EC000066 - Power contactor, AC switching |
| eClass | V11.0 : 27371003 |
| UNSPSC | 39121529 |
| E-Number (Finland) | 3707009 |

## Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

