Date: 25/04/2023

PGS23.063LM 30 60 barg 1/4 NPT

switchGAUGE PGS23.063

Item number:	48774057
Quantity:	1 pcs.
Order code:	PGS23.063.2.12ZI-8G460Z-NB-LM-30ZZZZIZ-ZZZZ ZZ 33D4EFSG0ZZZ-ZZZZZZ111Z
Overview:	PGS23.063LM 30 60 barg 1/4 NPT magnetic snap action switch, model 821.12 Electrical connection: 2 m cable Case: solid front design EN837 "S3" Connection location: LM class 1.6 Window: polycarbonate Ingress protection: IP 54 Permissible medium temperature: -20 ... +100 °C (-4 ... +212 °F) Pressure Gauge Standard: International (standard Europe) stop-pin at zero *WIKA* Serial number *...*
Details:	switchGAUGE PGS23.063 pressure gauge with switches, bourdon tube measuring system, stainless steel Specifications according to data sheet: PV 22.03 and AC 08.01 switch: magnetic snap action switch, model 821 first switch operation: makes (1) second switch operation: breaks (2) Electrical connection: 2 m cable Nominal size: 063 Measuring range: gauge pressure range Scale range: 0...60 barg Process connection: 1/4 NPT Connection location: lower mount Case: solid front design EN837 "S3" Pressure Gauge Standard: International (standard Europe) Accuracy class: class 1.6 Case material: Stainless steel 1.4301 Case surface: bare Window: polycarbonate Ingress protection: IP 54 Permissible medium temperature: -20 ... +100 °C (-4 ... +212 °F) Permissible ambient temperature: -20 … +60 °C Movement: stainless steel stop pin on dial: at zero Manufacturer logo: *WIKA*

© 2023 - WIKA Instruments s.a.r.l.

serial number on dial: Serial number *...*

© 2023 - WIKA Instruments s.a.r.l.