Date: 11/04/2023

S5550/union nut, conn. no.3, NS100, 0...80°C, L1=126 x6mm

Bimetal thermometer, stainless steel version

Item number:	48787738
Quantity:	1 pcs.
Order code:	S5550 -3-C1D-TD-B126G1Z-AHAZZZZ TB FZZZEZSVID-AZ1ZZZZZ1ZZZZ
Overview:	S5550/union nut, conn. no.3, NS100, 0...80°C, L1=126 x6mm Process connection: G 1/2 female flat instrument glass, liquid damping Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X) *WIKA* Serial number *...*
Details:	Bimetal thermometer, stainless steel version Specifications according to data sheet: TM 55.01 Case: stainless steel Stem material: stainless steel Model: S 5550, nominal size 100, adjustable stem and dial Accuracy class: class 1 per EN 13190 Connection design: 3, union nut Unit: °C Scale range: 0 °C ... 80 °C Process connection: G 1/2 female Stem diameter: 6 mm Insertion length L1: 126 mm Window: flat instrument glass Damping: liquid damping Zone: Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X) Case: Stainless steel Version: standard Stem material: stainless steel Ingress protection: IP 65 Permissible ambient temperature: -40 ... +70 °C Manufacturer logo: *WIKA* serial number on dial: Serial number *...* Explosion protection: ATEX Ignition protection type: Ex h

© 2023 - WIKA Instruments s.a.r.l.