Date: 22/04/2024

PCA4MA 1,6 … 10 bar 1/4 NPT-F , 1/2 -14 NPT-F

Compact pressure switch, flameproof Enclosure Ex d

Item number:	57386207
Quantity:	1 pcs.
Order code:	PCA4MA-BAEB-1ASZZZ1ZZ CZKW F4-C5- - - - -
Overview:	PCA4MA 1,6 … 10 bar 1/4 NPT-F , 1/2 -14 NPT-F Compact pressure switch, flameproof Enclosure Ex d PCA switch enclosure: stainless steel 316L Measuring elements and wetted parts: Diaphragm Inconel + O-Ring FPM Connection: Stainless steel AISI 316L contact version: 1xSPDT, silver contact 1,6 … 10 bar, working range -1 … 25 bar, proof pressure 40 bar Set point definition: Set Point not defined Process connection: 1/4 NPT-F Electrical connection: 1/2 -14 NPT-F standard direct or wall mounting, fixing bore on the case Ingress Protection: IP66 Brand: WIKA Instruments Italia Specifications according to data sheet: PV 33.31 Repeatability of set point: ≤ 1% of end of setting range
Details:	Compact pressure switch, flameproof Enclosure Ex d Model PCA Specifications according to data sheet: PV 33.31 Repeatability of set point: ≤ 1% of end of setting range switch enclosure: stainless steel 316L Measuring elements and wetted parts: Diaphragm Inconel + O-Ring FPM 1xSPDT, silver contact 1,6 … 10 bar, working range -1 … 25 bar, proof pressure 40 bar Set Point not defined Process connection: 1/4 NPT-F Electrical connection: 1/2 -14 NPT-F standard direct or wall mounting, fixing bore on the case Approvals / Certificates: with Brand: WIKA Instruments Italia Ingress Protection: IP66 PCA4MA 1,6 … 10 bar

© 2024 - WIKA Instruments s.a.r.l.