# DATASHEET - 7.2KV 125AMP 3" 'J' DIN FUSE



**Fuse-link, medium voltage, 125 A, AC 7.2 kV, 40 kA, 3", 76 x 292 mm, back-up, DIN, with striker**

Powering Business Worldwide

**Part no.** 7.2KV 125Amp 3" 'J' DIN Fuse
**Catalog No.** 7.2TFLSJ125

Similar to illustration

## Delivery program

| | | | |
|---|---|---|---|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | medium voltage |
| Rated current | I | A | 125 |
| Rated voltage | | | AC 7.2 kV |
| Construction size | | | 3" |
| Size | | | 76 x 292 mm |
| Utilization category | | | back-up |
| Status indicator | | | with striker |
| Breaking Capacity | | kA | 40 |
| usable for size/applications | | | transformer protection<br>indoor or outdoor use |
| Standard/Approval | | | DIN |
| Standards/Regulations | | | DIN 43625<br>VDE 0670-4<br>VDE 0670-402<br>IEC 60282-1 |

## Technical data ETIM 7.0

| Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507) | | | |
|---|---|---|---|
| Rated current | | A | 25 |
| Rated voltage | | kV | 7.2 |
| Voltage type | | | AC |
| Rated frequency | | Hz | 50 - 50 |
| Breaking capacity | | kA | 40 |
| Utilization category | | | Other |
| Application | | | Primary side transformer protection |
| Length | | mm | 292 |
| Diameter | | mm | 76 |
| Performance category according to IEC 60282-1 | | | Back-up |
| With striker | | | Yes |
| Standard | | | DIN |
| Release characteristic | | | Other |
| Installation technique | | | Air |


© 06/2021 by Eaton Industries GmbH