# Specifications







## Eaton EVMAF332A

Eaton Managed G4 Rack PDU, 0U, 39U, IEC-60309 input, 3m cord, 3ph, 22kW, 32A, 415/240V, 24 outlets (12)C13, (12)C39

| General specifications | |
|---|---|
| **PRODUCT NAME** | Eaton Rack PDU G4 |
| **CATALOG NUMBER** | EVMAF332A |
| **MODEL CODE** | PDU G4 MA 0U 309 32A 3P 12xC13,12xC39 |
| **EAN** | 3553340696978 |
| **PRODUCT LENGTH/DEPTH** | 1730 mm |
| **PRODUCT HEIGHT** | 53 mm |
| **PRODUCT WIDTH** | 52 mm |
| **PRODUCT WEIGHT** | 5.8 kg |
| **COMPLIANCES** | CB<br>LVD Directive<br>RoHS Directive<br>WEEE Directive<br>Packaging Directive<br>EMC Directive |
| **CERTIFICATIONS** | IEC 62368-1<br>EN IEC 63000<br>CE<br>EAC<br>UKCA<br>Cm<br>Ukr<br>IEC/EN 61000-6-2<br>IEC/EN 61000-6-4<br>CISPR 35/EN 55035<br>IEC 61000-3-11<br>IEC 61000-3-12 |

Powering Business Worldwide

## Electrical input

| | |
|---|---|
| **INPUT CONNECTION** | IEC-60309 32A 3Ph |
| **WATTAGE** | 22 kW max |
| **AMPERAGE RATING** | 32 A |
| **INPUT VOLTAGE** | 240/415V |
| **PHASE** | Three-phase |
| **CIRCUIT BREAKER** | (6) single-pole |
| **FREQUENCY RATING** | 50/60 Hz |
| **CORD LENGTH** | 3m |

## Electrical output

| | |
|---|---|
| **OUTLETS** | (12) C13, (12) C39 |
| **NUMBER OF OUTPUTS C13** | 12 |
| **NUMBER OF OUTPUTS C19** | 12 |
| **NUMBER OF OUTPUTS (OTHER)** | 12 |
| **NUMBER OF OUTLETS WITH EARTH PIN** | 24 |

## Technology & communications

| | |
|---|---|
| **TYPE** | Managed Rack PDU |
| **OUTLET CONTROL** | Yes |
| **SPECIAL FEATURES** | • Remote Site Management<br>• Versatile C39 outlet supports C14 or C20 power cord plug<br>• High retention outlets designed to securely fit standard power cords and support P-Lock power cords<br>• Cybersecurity standards UL 2900-1 and IEC 62443-4-2<br>• Hot-Swap network control module<br>• Network Cascading, connect up to 32 PDUs via network loop<br>• Power sharing between two network modules PDUs ensures constant access to PDU data & sensors<br>• 1% IEC Class 1 billing grade measurement accurancy<br>• Gigabit network card with 2x Gb ports<br>• Support protocols RestAPI, Modbus TCP, SNMP, LDAP, HTTPS<br>• 1% measurement accuracy at the outlet level (V, W, A)<br>• Outlets control for On/Off, reboot, and sequential start-up capabilities |
| **ETHERNET INTERFACE** | Yes |
| **SERIAL INTERFACE** | Yes |

## Additional specifications

| | |
|---|---|
| **OPERATING TEMPERATURE** | 0° to 60°C (32° to 140°F) |
| **ACCESSORIES** | • Rack PDU<br>• Rack mounting accessories<br>• Quickstart guide<br>• Safety Instructions |
| **MATERIAL** | Aluminium |
| **COLOR** | Black |

| | |
|---|---|
| **SNMP** | Yes |
| **MASS CONFIGURATION** | Yes |

## Resources

| | |
|---|---|
| **BROCHURES** | Rack PDU G4 Brochure EN |
| **DECLARATIONS OF CONFORMITY** | EU declaration of conformity Rack PDU G4 |
| **DRAWINGS** | EVMAF332A-en-us |

| | |
|---|---|
| **PROJECT NAME:** | |
| **PROJECT NUMBER:** | |
| **PREPARED BY:** | |
| **DATE:** | |

**Eaton Corporation plc**
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.